

## Biamp Desono COLW101 White - Nazidni zvučnik

Šifra: 18421  
Kategorija proizvoda: Outdoor Zvučnici  
Proizvođač: Biamp

**Cena: 59.880,00 rsd**

Operating Mode: Passive  
Operating Environment: Indoor/Outdoor  
Operating Range (-10dB): 165 Hz to 18 kHz  
Nominal Beamwidth (H x V): 100° x 8°  
Transducers: LF 10 x 3.3" (84 mm) coated paper cone / HF 1 x 1" (25 mm) soft dome  
Continuous Power Handling @ Nominal Impedance: 28V 100W @ 8Ω (400W peak)  
Nominal Sensitivity: 99 dB  
Nominal Maximum SPL: Peak 125 dB, Continuous 119 dB  
Transformer 70V: 100W, 50W, 30W, 20W / 100V: 100W, 60W, 40W  
Recommended Amplifiers: 100W - 200W @ 8Ω (28V - 40V)

Input Connection: Multi-position pass-through, screw-down terminal block  
Controls: None; select transformer tap or low impedance input via terminal block wiring  
Mounting Provisions: Adjustable tilt L-bracket  
Environmental: IP66 per IEC 60529  
Dimensions H x W x D: 46.5" x 3.9" x 3.3" (1180 mm x 100 mm x 83 mm)  
Weight: 17 lbs (7.7 kg)  
Finish: Refer to the Technical Drawings (page 3)  
Accessories (included): L-brackets and 2x IP66 water-tight gland nuts

### APPLICATIONS

Houses of Worship · Retail Outlets · Hotels  
Bars and Restaurants · Courtrooms ·  
Auditoria · Theaters · Museums · Airports  
Corporate Meeting Rooms

### DESCRIPTION

The Desono COLW101 two-way 10 x 3.3" column loudspeaker is an excellent choice when sonic clarity and predictable directional control are required from an unobtrusive loudspeaker designed to blend in with the background.

The highly-focused dispersion pattern and improved speech intelligibility of the COLW101 enables it to excel in reverberant

environments like houses of worship and auditoria, while its weather-resistant construction allows it to be used in outdoor applications such as patios or concourses. The COLW101 utilizes a 4-position switchable transformer ranging from 20W to 100W with low-impedance bypass for constant-voltage operation, making it an excellent choice for large areas of BGM.

The Desono COLW101 is an excellent choice for both indoor and outdoor distributed audio applications that need speech intelligibility and background