Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

# Biamp Desono EX-S10SUB-CM-B Black - Pasivni vufer



Šifra: 18428
Kategorija prozivoda: Nazidni Zvučnici
Proizvođač: Biamp

## Cena: 113.880,00 rsd

| | |
|---|---|
| **Operating Mode** | Passive, low impedance |
| **Operating Environment** | Indoor/Outdoor |
| **Operating Range (-10dB)** | 38 Hz to 140 Hz |
| **Nominal Beamwidth (H x V)** | Omnidirectional |
| **Transducers** | LF 1 x 10" (250 mm) treated paper cone |
| **Sensitivity @ 1 m** | 89 dB (2.83 V)<br>89 dB (1 W, 8 Ω nominal impedance) |
| **Nominal Continuous Power Handling** | 49 V (300 W, 8 Ω) |
| **Nominal Maximum SPL (Processed) @ 1 m** | UXO 80 Hz: Continuous 112 dB Peak 118 dB<br>UXO 125 Hz: Continuous 113 dB Peak 119 dB |
| **Rated Continuous Voltage** | 39.8 V (32 dBV) |
| **Rated Maximum SPL (Processed) @ 1 m** | UXO 80 Hz: Continuous 110 dB Peak 122 dB<br>UXO 125 Hz: Continuous 111 dB Peak 123 dB |
| **Required Processing** | 35 Hz, 18 dB high-pass filter; DSP preset |
| **Recommended Amplifiers** | 300 W - 600 W, 8 Ω (49 V - 69 V) |

| | |
|---|---|
| **Input Connection** | Lever-actuated wire clamping 4-position terminal block with pass-through |
| **Controls** | None |
| **Mounting Provisions** | ClickMount pan-tilt bracket or ClickMount U-Bracket |
| **Compliance** | ETL listed to comply with UL 1480A, CSA STD C22.2# 62368-1 |
| **Environmental Rating** | IP54 per IEC 60529, IEC 60068-2-5 (Solar Radiation)<br>IEC 60068-2-11 (Salt Mist), IEC 60068-2-42 (SO2)<br>IEC 60068-2-60 (Chlorine) |
| **Dimensions H x W x D** | 529 mm x 310 mm x 312 mm [20.8" x 12.2" x 12.3"] |
| **Weight (loudspeaker only)** | 12.8 kg [28.26 lbs] |
| **Finish** | High-impact UL94 5VB rated polycarbonate/ABS blend, painted UV resistant matte finish<br>Bracket: Heavily reinforced glass-filled nylon with UV-resistant painted matte finish cover<br>Color: Black (RAL 9017) or White (RAL 9016) |
| **Grille** | Powder-coated perforated Marine Grade aluminum backed with hydrophobic cloth<br>Black or White |
| **Models (Order by mounting option)** | EX-S10SUB-CM [-B,-W] - loudspeaker with large ClickMount pan-tilt bracket<br>EX-S10SUB-UB [-B,-W] - loudspeaker with ClickMount U-Bracket and ClickPlug |
| **Options** | CMX-LG [-B,-W] - Large ClickMount Pan-tilt Bracket Kit<br>EXUB-S10 [-B,-W] - EX-S10 ClickMount U-Bracket kit |

## Description

The Desono EX-S10SUB, 10 inch subwoofer provides additional deep base to the EX-S6 or EX-S8 systems for full-range, foreground music playback. With its discreet matching enclosure, EX-S10SUB easily blends in the background of an application, making it easy to hear, but difficult to spot.

Designed for easy and fast installation, our innovative, patented ClickMount™ brackets provide installers with two distinct mounting options. The ClickMount pan-tilt bracket provides indexed aiming control and allows for mounting EX Series quickly in either vertical or horizontal orientation without moving the bracket position. The ClickMount U-Bracket is also available for low profile mounting or exterior use and includes the ClickPlug with an integrated gland nut for weather-resistant applications. Both brackets are theft and tamper resistant.

**Features:**

Exceptional audio clarity with discreet styling

Easy to install with two mounting options

Low frequency boost for distributed applications

ETL listed to comply with UL 1480A, CSA 62368-1, CE marked, and RoHS compliant

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.