Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

FBT MITUS 210MA

Šifra: 10779
Kategorija prozivoda: Aktivne Zvučne Kutije
Proizvođač: FBT



Cena: 209.880,00 rsd

2-way bi-amplified, bass-reflex design with coaxial driver
2 x 250 mm (2 x 10’’) B&C custom neodymium magnet speakers with 64 mm (2.5’’) voice coil, one of them is coaxial with 36 mm (1.4’’) exit titanium compression driver and 64 mm (2.5’’) voice coil
Frequency response from 60Hz to 20KHz
Class D built-in amplifiers, 600WRMS to the LF and 300WRMS to the HF with switch mode power supply
DSP with 8 eq presets
Control panel with XLR input and link, volume, presets, HP-filter, ground-lift
70° conical dispersion
15 mm (5/8”) birch plywood enclosure, scratch resistant black paint finish
35 mm (1.38’’) stand socket and back side carrying handle
Ideal for live sound stage monitoring applications, as well as a front of house main PA speaker
Very lightweight, only 19Kg

Configuration: 2 Way
Frequency response: 60Hz - 20kHz
Low frequency woofer: 2x 10" with 2.5" VC
High frequency driver: 1x 1.4" with 2.5" VC
Maximum SPL cont/peak: 127 / 134dB
Dispersion: 70 x 70 conical (HxV)
Input impedance: 22kohm
Crossover frequency: 1.2 kHz
Input connector: XLR with link out
Net Dimension (WxHxD): 547 x 290 x 402mm
Net Weight: 19kg
Transport Dimension (WxHxD): 890 x 390 x 510m
Transport Weight: 21.2kg
AC Power requirements: 640VA
Built-in amplifier LF/HF: 600/300w RMS
Built-in amplifier peak LF/HF: 1200/600w
Power cord: 5m PowerCon

The FBT MITUS 210MA bi-amplified speaker feature 0.59" birch plywood construction; the front shall be protected by a heavy duty metal grille with anti-resonance spacers and exclusive synthetic cloth to protect the drivers and a rugged touring grade scratch resistant black paint finish protects the cabinet exterior.

The FBT MITUS 210MA is a two way coaxial design incorporating 2x 10" B&C custom neodymium

magnet coaxial speaker with 2.5" voice coil and 1.4" exit titanium compression driver with 2.5" voice coil, a class D built-in amplifiers 600W RMS to the LF and 300W RMS to the HF with switch mode power supply.

The FBT MITUS 210MA provides a DSP with A/D-D/A low noise converters with 8 selectable presets. The FBT MITUS 210MA shall meet the following performance criteria: Frequency response of 60Hz to 20kHz, Maximum SPL of 132dB, Nominal impedance 8 Ohm LF / 8 Ohm HF. The control panel provides XLR «in&link», volume, preset, HP filter, GND lift switch.
A standard 1.38" speaker stand socket allows the FBT MITUS 210MAto be mounted on speaker stand.

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.