

Mackie DLM12S - Aktivni sabvufer

Šifra: 18530
Kategorija proizvoda: Aktivni Subwooferi
Proizvođač: MACKIE

Cena: 143.880,00 rsd



Class D 1,000W RMS Powered Subwoofer
2,000W Peak Power
Generates up to 128dB SPL
Frequency Response Down to 35 Hz
DLP Digital Processor
Precision Digital Variable Crossover
Flexible Connectivity
Compact Design and Durable Construction

PA Speaker

Configuration	Active Subwoofer
Total Power Capacity	1000 W RMS 2000 W Peak
Amplifier Class	Class-D

Drivers

LF Driver	1x 12" / 305 mm Woofer
LF Voice Coil	3" / 76 mm
Magnet	Ferrite

Performance

Frequency Response	35 Hz to 135 Hz -10 dB
Maximum SPL	128 dB
I/O Impedance	Input: 20 Kilohms (Balanced) 10 Kilohms (Unbalanced)
Total Harmonic Distortion/Noise	< 1%

Connectivity

Audio I/O	2x XLR 3-Pin Balanced Input 2x XLR 3-Pin Balanced Output 2x XLR 3-Pin Balanced High-Pass Output
-----------	---

Signal Processing

Crossover	60 to 120 Hz
Alignment Delay	0 to 300 ms

Power

AC Input Power	100 to 120 VAC, 50 / 60 Hz 220 to 240 VAC, 50 / 60 Hz
AC Power I/O	1x IEC
Power Consumption	250 W

Physical

Handles	2x Side
Cooling	Fan (Variable Speed)
Construction Material	Metal Grille, Wood

Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	17.9 x 16.4 x 20.8" / 455 x 417 x 529 mm
Weight	48 lb / 21.7 kg

Packaging Info

Package Weight	58.2 lb
Box Dimensions (LxWxH)	27.5 x 23.5 x 23"