

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Mackie SRM150 type unknown

For

Mackie SRM150

Šifra: 18527

Kategorija proizvoda: Aktivne Zvučne Kutije

Proizvođač: MACKIE

Cena: 35.880,00 rsd

Includes Power Cord

Boardroom A/V to Live Music
Portable Powered Loudspeaker System
3-Channel Mixer with 3-Band EQ
Two Mic/Line Preamps with 48V
Hi-Z Input for Instruments
Dedicated Stereo Line-Level Channel
Built-In Limiter for System Protection
Mic Stand Integration System
Lightweight at 7.6 lb

Key Specs

Speaker Configuration	1x Full-Range Loudspeaker
Number of Input Channels	3 (2 x Mono, 1 x Stereo)
Amplifier Power Rating	150 W
Audio I/O	1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input 1x Combo XLR-1/4" TRS Mic/Line Input 1x Combo XLR-1/4" TRS Line Input 1x Stereo RCA TS Input 1x XLR 3-Pin Male Mic/Line Thru

Portable PA System

Speaker Configuration	1x Full-Range Loudspeaker
Number of Input Channels	3 (2 x Mono, 1 x Stereo)
Amplifier Power Rating	150 W
Amplifier Class	Class-D

Speakers

Full-Range Driver	5.25" / 133.35 mm Cone
Magnet	Neodymium

Signal Processing

Input Pad	No
EQ	Contour: ±15 dB at 12 kHz (on Master) ±15 dB at 2.5 kHz (on Master) ±15 dB at 100 Hz (on Master)

Performance

Frequency Response	100 Hz to 17.5 kHz -3 dB
Frequency Range	60 Hz to 22 kHz -10 dB
Maximum SPL	120 dB (Peak)
I/O Impedance	Mic Input: 3 Kilohms (Balanced) Hi-Z Input: 20 Kilohms (Balanced) Line Input: 10 Kilohms (Balanced)
THD	0.05%
Protections	AC Fuse, Output Limiter

Connectivity

Audio I/O	1x Combo XLR-1/4" TRS Balanced/Unbalanced Mic/Line/Hi-Z Input 1x Combo XLR-1/4" TRS Mic/Line Input 1x Combo XLR-1/4" TRS Line Input 1x Stereo RCA TS Input 1x XLR 3-Pin Male Mic/Line Thru
Phantom Power	+48 V (Switchable)

Power

AC Input Power	100 to 240 VAC, 50 / 60 Hz
AC Power I/O	IEC Input

Physical

Transport Options	Handle (Top)
Mounting	1 x Mic Stand Socket (Bottom)
Construction Material	Polypropylene
Environmental Protection	No
Operating Temperature	32 to 104°F / 0 to 40°C
Dimensions	11.2 x 8 x 6.8" / 28.4 x 20.3 x 17.3 cm
Weight	7.6 lb / 3.4 kg