

## SYNQ SE-1100

Šifra: 18758  
Kategorija proizvoda: Razglasna Pojačala  
Proizvođač: SYNQ



**Cena: 45.480,00 rsd**

<b>General : Dimensions (cm)</b>	48.2 x 6.6 x 21.5
<b>General : Weight (kg)</b>	3.85
<b>General : Color</b>	black
<b>General : Powerinput</b>	AC 230V, 50Hz
<b>General : Energy Label</b>	No
<b>General : Power consumption W</b>	1200
<b>General : Display</b>	No
<b>General : Fixation</b>	19" rack mountable

<b>General : RU</b>	1.5U
<b>General : IP rating</b>	indoor
<b>Audio : min. frequency (Hz)</b>	20
<b>Audio : max. frequency (Hz)</b>	20000
<b>Audio : S/N ratio (&gt; dB)</b>	103
<b>Audio : damping factor (&gt;...)</b>	400
<b>Audio : max. output channels</b>	2
<b>Audio : Wrms 4Ω stereo, per channel</b>	550
<b>Audio : Wrms 8Ω stereo, per channel</b>	300
<b>Audio : Wrms 8Ω bridge</b>	1100
<b>Audio : functions</b>	bridge mode, limiter
<b>Connections : input</b>	3 pin XLR, PowerCon® or compatible
<b>Connections : output</b>	3 pin XLR, speakon

This SE-1100 power amplifier is unprecedented in terms of price / performance.

The sophisticated design of this lightweight CLASS-D amplifier ensures excellent and powerful low-frequency reproduction combined with crystal clear and delicately balanced high frequencies.

Thanks to the big power reserve, excellent limiters and protections it can be used in all kinds of different applications such as discotheques, clubs, mobile audio, PA, rental, theater, ...

The extremely high efficiency, reduced power waste and very low heat dissipation are the main advantages of this compact amplifier!

Incredible space savings for mobile applications: depth of the 1.5U enclosure is only 21cm!

Incredibly low weight, only 3,85kg!

Power output, stereo:

2x 300Wrms @ 8  $\Omega$

2x 550Wrms @ 4  $\Omega$

Power output, bridge:

1x 1100Wrms @ 8  $\Omega$

All the protections you can think of for professional use:

Inaudible signal + current limiter

Overload protection

Short circuit current protection

DC protection

Thermal protection

AC / VHF protection

Soft start

...

3 different working modes: stereo, bridge mode, mono mode (inputs linked)

Input sensitivity: 0,7 V / 1 V / 1,4 V

Balanced in/outputs on XLR

2 Speakon® compatible connectors (left and right outputs)

1 separate output for bridge mode