

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

SYNQ SE-1800 type unknown

SYNQ SE-1800

Šifra: 18757
Kategorija proizvoda: Razglasna Pojačala
Proizvođač: SYNQ

Cena: 79.080,00 rsd

48.2 x 8.8 x 36.5

General : Dimensions (cm)

General : Weight (kg)

9.34

General : Color

black

General : Powerinput

AC 230V, 50Hz

General : Energy Label

No

General : Display

LCD

General : Fixation

19" rack mountable

General : RU

2U

General : IP rating

indoor

Audio : min. frequency (Hz)	20
Audio : max. frequency (Hz)	20000
Audio : S/N ratio (> dB)	100
Audio : damping factor (>...)	800
Audio : max. output channels	2
Audio : Wrms 2Ω stereo, per channel	1200
Audio : Wrms 4Ω stereo, per channel	900
Audio : Wrms 8Ω stereo, per channel	600
Audio : Wrms 4Ω bridge	2400
Audio : Wrms 8Ω bridge	1800
Audio : functions	bridge mode, limiter
Connections : input	3 pin XLR, jack, PowerCon® or compatible
Connections : output	3 pin XLR, speakon

The SE-1800 power amplifier is unprecedented in terms of price / performance.

The sophisticated design of this lightweight CLASS-TD amplifier ensures excellent and powerful low-frequency reproduction combined with crystal clear and delicately balanced high frequencies.

Thanks to the big power reserve, excellent limiters and protections it can be used in all kinds of different applications such as discotheques, clubs, mobile audio, PA, rental, theater, ...

The extremely high efficiency, reduced power waste and very low heat dissipation are the main advantages of this compact amplifier!

The 2U enclosure weighs only 9.34 kg, which makes it perfect for mobile applications!

The LCD-display shows: audio input level, mains voltage, working temperature and fan speed.

Power output, stereo:

2x 600Wrms @ 8 Ω

2x 900Wrms @ 4 Ω

2x 1200Wrms @ 2 Ω

Power output, bridge:

1x 1800Wrms @ 8 Ω

1x 2400Wrms @ 4 Ω

All the protections you can think of for professional use:

Inaudible signal + current limiter

overload protection

short circuit current protection

DC protection

thermal protection

AC / VHF protection

soft start

...

Two FAN modes:

Silent mode: minimum fan noise for use in recording studio, theatre, ...

Power mode: maximum cooling for use in rough conditions like discotheques, summer festivals, ...

3 different working modes: stereo, bridge mode, mono mode (inputs linked)

Input sensitivity: 0,75V / 1,0V / 1,5 V

Balanced in/outputs on XLR / COMBO

2 Speakon® compatible connectors (left, right & bridge outputs)