

SYNQ SE-3000

Šifra: 18756
Kategorija proizvoda: Razglasna Pojačala
Proizvođač: SYNQ



Cena: 95.880,00 rsd

General : Dimensions (cm)	48.2 x 8.8 x 36.5
General : Weight (kg)	10.06
General : Color	black
General : Powerinput	AC 230V, 50Hz
General : Energy Label	No
General : Display	LCD
General : Fixation	19" rack mountable
General : RU	2U

General : IP rating	indoor
Audio : min. frequency (Hz)	20
Audio : max. frequency (Hz)	20000
Audio : S/N ratio (> dB)	100
Audio : damping factor (>...)	800
Audio : max. output channels	2
Audio : Wrms 2Ω stereo, per channel	2000
Audio : Wrms 4Ω stereo, per channel	1500
Audio : Wrms 8Ω stereo, per channel	1000
Audio : Wrms 4Ω bridge	4000
Audio : Wrms 8Ω bridge	3000
Audio : functions	bridge mode, limiter
Connections : input	3 pin XLR, jack, PowerCon® or compatible
Connections : output	3 pin XLR, speakon

The SE-3000 power amplifier is unprecedented in terms of price / performance.

The sophisticated design of this lightweight CLASS-TD amplifier ensures excellent and powerful low-frequency reproduction combined with crystal clear and delicately balanced high frequencies.

Thanks to the big power reserve, excellent limiters and protections it can be used in all kinds of different applications such as discotheques, clubs, mobile audio, PA, rental, theater, ...

The extremely high efficiency, reduced power waste and very low heat dissipation are the main advantages of this compact amplifier!

The 2U enclosure weighs only 10 kg, which makes it perfect for mobile applications!

The LCD-display shows: audio input level, mains voltage, working temperature and fan speed.

Power output, stereo:

2x 1000Wrms @ 8 Ω

2x 1500Wrms @ 4 Ω

2x 2000Wrms @ 2 Ω

Power output, bridge:

1x 3000Wrms @ 8 Ω

1x 4000Wrms @ 4 Ω

All the protections you can think of for professional use:

Inaudible signal + current limiter

overload protection

short circuit current protection

DC protection

thermal protection

AC/VHF protection

soft start

...

Two FAN modes:

Silent mode: minimum fan noise for use in recording studio, theatre, ...

Power mode: maximum cooling for use in rough conditions like discotheques, summer festivals, ...

3 different working modes: stereo, bridge mode, mono mode (inputs linked)

Input sensitivity: 0,75V / 1,0V / 1,5 V

Balanced in/outputs on XLR / COMBO

2 Speakon® compatible connectors (left, right & bridge outputs).