

## FBT VENTIS 110A - Aktivni zvučnik

Šifra: 18819

Kategorija prozivoda: Aktivne Zvučne Kutije

Proizvođač: FBT

**Cena: 103.800,00 rsd**

Net Dimension (WxHxD): 329 x 575 x 325mm

Net Weight: 15.6kg

Transport Dimension (WxHxD): 420 x 675 x 400

Transport Weight: 18.1kg

AC Power requirements: 640VA

Built-in amplifier LF/HF: 900w (700w LF + 200w HF)

Built-in amplifier peak LF/HF: 1800w (1400w LF + 400w HF)

Power cord: 5m Neutrik True1

Built in amplifier: 900w (700w LF + 200w HF)

Built in amplifier peak: 1800w (1400w LF + 400w HF)

Maximum SPL continuous/peak: 124/131dB

Dispersion (HxV): 80° x 50° rotatable

### FBT VENTIS 110A - Aktivni zvučnik

Configuration: 2 Way

Frequency response: 58Hz - 20kHz -6dB

Low frequency woofer: 10" / 2" coil

High frequency driver: 1" / 1.4" coil

Maximum SPL cont/peak: 124/131dB

Dispersion: 80 x 50 Rotatable

Input impedance: 22kOhm

Input connector: XLR/Jack Combo socket with XLR link out, RCA stereo input

### KEY FEATURES

2-way, bi-amplified, bass reflex design

Biamped: 700W RMS LF and 200W RMS HF power amplifiers in Class D for LF and in Class H/AB for HF

Digital Signal Processor with graphic display

15 mm (0.59") birch plywood scratch resistant enclosure and internal bracing

High efficiency switch mode power supply

Control Panel features balanced XLR/Jack input, XLR LINK OUT, 2 x Volume, RCA Stereo input, DSP display with rotative encoder and push

250mm (10") LF woofer with 50mm (2") voice coil, custom made for FBT

25mm (1") exit throat B&C HF compression driver with 36mm (1.4") voice coil

Frequency response from 58Hz to 20 kHz

80°H x 50°V Constant Directivity Rotatable Horn

6 x M10 suspension points, optional wall bracket mount thread, 35mm (1 3/8") top-hat

Speaker stand socket, one aluminium handle

45° monitor taper

Adjustable delay between 0 - 10m

Weight : 15.6Kg

Dimensions : 329 x 575 x 325mm

### PRODUCT DESCRIPTION

PROCESSED ACTIVE SPEAKER 700W + 200W RMS - 131DB SPL

For the VENTIS range, quality and flexibility are the watchwords. Based on a powerful combination of B&C compression drivers and FBT's own custom, long excursion woofers, the 115, 112 and 110 models are two-way, bass reflex designs housed in 15mm birch plywood. A full-grille design backed by specially treated acoustic cloth delivers the characteristic style for which FBT is known, while fully rotatable constant directivity horns ensure accurate coverage.

## **VENTIS Presets**

The FBT VENTIS range offers powerful DSP with 6 versatile presets. Crafted by expert FBT engineers, the presets offer a performance for every requirement.

**ORIGINAL / LIVE** The renowned, smooth FBT sound

**VOCAL** A special EQ setting to maximise speech intelligibility

**DJ** Designed to keep the energy high and your audience dancing

**TOURING** The reliability and the roar of the industry's most popular touring systems

**LOUDNESS** The ultimate preset for listening at a medium or low volume

**WARM** A special setting to emphasise full-bodied, low-mid frequencies.