

FBT X-LITE 110 Pasivni zvučnik

Šifra: 18820

Kategorija proizvoda: Pasivne Zvučne Kutije

Proizvođač: FBT

Cena: 39.480,00 rsd



Configuration: 2

Recommended amplifier: 350W RMS

Long Term power: 175W

Short term power: 700W

Nominal impedance: 8Ohm

Frequency response: 65Hz - 20kHz

Low Frequency woofer: 10 - 2.5 coil inch

High frequency driver: 1 - 1.4 coil inch

Sensitivity (@1W/1m): 96dB

Maximum SPL cont/peak: 121 / 124dB

Dispersion: 90° x 60° HxV

Crossover Frequency: 2kHz

Recommended HP filter: HP 55Hz - 12/24 dB oct.

Recommended external filter: FBT DSP Processor

Input connector: 2 x Speakon

Net Dimension (WxHxD): 300 x 536 x 301,5 mm / 11,81 x 21,10 x 11,87 inch

Net Weight: 14,5 Kg / 31,96 Lb

The asymmetrical shape of the FBT X-LITE 110 cabinet also allows use as a floor stage monitor. The FBT X-LITE 110 is two way design incorporating an 10" low frequency woofer and 1" HF compression driver coupled to a 90°H x 60°V constant directivity horn. With a frequency range of 65Hz - 20kHz the FBT X-LITE 110 speakers provide high fidelity sound for both speech and music applications with a maximum SPL of 124dB.

Ideal for small fixed installations the FBT X-LITE 110 speaker have an impedance of 8 Ohm and the internal crossover is at a fixed frequency of 2kHz. The control panel features 2 x NL4 Neutrik speakon. 4 x M10 rigging points built into the cabinet along with the optional mounting brackets allow the FBT X-LITE 110 speaker to be surface mounted on walls or ceilings. A standard 1,38" speaker stand socket allows the FBT X-LITE 110 to be mounted on speaker stand. A front face steel grille protects the speaker from external damage.