

## Saramonic BlinkMe U2

Šifra: 18930

Kategorija proizvoda: Wireless Mikrofoni

Proizvođač: Saramonic



**Cena: 46.800,00 rsd**

### Transmitter

Display □ TFT

Transmission Type □ 2.4GHz digital frequency

Modulation □ Digital modulation

Polar Pattern □ Omnidirectional

Antenna □ Built-in antenna

Operating Range (without obstacles) □ 328" (100m)

RF Output Power □ <10mW

Sampling Rate □ 48KHz

Frequency Response □ 20Hz-20KHz

Signal-to-Noise Ratio □ >80dB

Maximum SPL □ 110dB SPL

Sensitivity □ -39±2dB

Audio Input Connector □ Built-in condenser microphone

Power Requirements □ Built-in rechargeable lithium-ion battery

Battery Specification □ 3.85V/495mAh

Charging Connector □ Charging contacts

Battery Life □ Approx. 5 hours (onboard recording enabled) / Approx. 8 hours (onboard recording disabled)

Memory □ 8GB

Weight □ 1.06oz (30g)

Dimensions □  $\phi$ 1.85" × 0.49" ( $\phi$ 47mm × 12.5mm)

Operating Temperature □ 0°C to +50°C

Storage Temperature □ -10°C to +50°C

### Receiver

Transmission Type □ 2.4GHz digital frequency

Modulation □ Digital modulation

Antenna □ PIFA

Operating Range □ Up to 100m (Without Obstacle)

Frequency Response □ 20Hz-20kHz

Audio Output □ RXUC: USB-C digital output / RXDi: iOS Lightning digital output

Power Requirements □ Powered by an external device

Weight □ RXUC: 11.3g / RXDi: 11.2g

Dimensions □ 5.45mm × 22.88mm × 8mm

Operating Temperature □ 0°C to +50°C

Storage Temperature □ -10°C to +50°C

### Charging Case

Battery Voltage / Capacity □ 3.7V / 3000mAh

Charging Time□Approx.2.5hours  
Charging Connector□USB-C port (5V/3A)  
Times for Charging Microphone□2times (2\*TX)  
Weight□193.8g  
Dimensions□138.50mm×66.58mm×34.38mm  
Operating Temperature□0°C to +50°C  
Storage Temperature□-10°C to +50°C

### **Packing List**

BlinkMe TX Transmitter \*2  
BlinkMe RXUC Receiver \*1  
BlinkMe RXDi Receiver \*1  
BlinkMe CC Charging Case \*1  
Magnetic Clip \*2  
Magnet \*2  
Fur Windshield \*2  
USB-A to USB-C Cable \*1  
USB-C Male to 3.5mm TRS & USB-C Female Audio Cable \*1  
Screen Protector for Transmitter \*2