

MARTIN AUDIO BLACKLINE X218SUB

Šifra: 19053

Kategorija proizvoda: Pasivni Subwooferi

Proizvođač: Martin Audio

Cena: 227.880,00 rsd



Features

- Dual-driver, direct radiator subwoofer
- 2 x 18" (460mm) drivers with 4" (100mm) voice coils
- Durable plywood enclosure
- Large ports for reduced air noise
- Powder coated, perforated steel grille
- Integral ergonomic handles
- 35mm pole-mount socket
- Feet for vertical or horizontal operation
- Rebate recesses for stable horizontal stacking
- M10 flying inserts

Applications

- Portable sound reinforcement
- Live music clubs
- Bars and restaurants
- Nightclubs
- Corporate AV events and conferences
- Weddings and parties
- Secondary stages at festivals
- HoW, leisure centres and retail outlets

TYPE Dual-driver, direct radiating subwoofer
FREQUENCY RESPONSE (5) 42Hz-200Hz \pm 3dB, -10dB @ 33Hz
DRIVER 18" (460mm)/4" (100mm) voice coil, long excursion, ferrite magnet
RATED POWER (2) 1600W AES, 6400W peak
SENSITIVITY (8) 106dB
MAXIMUM SPL (9) 141dB peak (half space)
NOMINAL IMPEDANCE 4 Ω
DISPERSION (-6dB) Omnidirectional
CROSSOVER 80-120Hz active
ENCLOSURE Birch/poplar ply
FINISH Black textured paint
PROTECTIVE GRILLE Black perforated steel
CONNECTORS 2 x NL4 type
PIN CONNECTIONS (INPUT) 1+ 1- Link Through 2+ 2-

PIN CONNECTIONS (LINK) 1+ 1- Link Through 2+ 2-
FITTINGS 12 x M10 inserts, pole-mount socket
DIMENSIONS

(W) 1049mm x (H) 587mm x (D) 727mm

(W) 41.3ins x (H) 23.1ins x (D) 28.6ins

WEIGHT 88kg (194lbs)

Architectural Specs

Martin Audio Blackline X218

The loudspeaker shall be a dual-driver subwoofer consisting of two 18" reflex-loaded, long-excursion, low frequency transducers.

The on-axis frequency response shall be 42Hz-200Hz +/- 3dB and the loudspeaker shall produce a maximum SPL of 141dB peak in half space calculated at 1 metre. Power handling shall be 1600W AES, 6400W peak. Rated impedance shall be 4 ohms. The rear connector panel shall be fitted with two NL4 type connectors and the loudspeaker shall be operated in conjunction with a dedicated electronic controller or amplifier with onboard DSP.

The enclosure shall be made from plywood and finished with a black textured paint. The enclosure shall be fitted with a pole-mount socket and M10 threaded inserts for eyebolt suspension of a single enclosure. Provision shall be made for the fitment of castors and the drivers shall be protected by a perforated steel grille.

Dimensions (W x H x D) including feet shall be 1049mm x 587mm x 727mm (41.3in x 23.1in x 28.6in).

Weight shall be 88kg (194lbs).

The loudspeaker shall be the Martin Audio X218.