

Biamp MAX Connect - Media razdelnik

Šifra: 19057
Kategorija proizvoda: Evoko Booking System
Proizvođač: Biamp

Cena: 300.000,00 rsd

- Make UC calls from own device
- A participant who hosts a UC call can share all the content presented on the room display with remote participants
- Participants can replace the room camera view with their device camera view to frame objects, a physical whiteboard, or themselves during UC call
- Manage collaboration sessions, UC calls, through included handheld remote control, the optional Touch 8 MAX control panel, or through touch-enabled AV room display
- Connected Biamp AV peripherals (including Vidi 250, Parlé VBC/ABC 2500 and 2500a) can be controlled and, when compatible, optimized using Biamp Launch* — all from MAX Connect interfaces
- Monitoring, updating, and configuring of MAX Connect and Biamp connected peripherals are available through Biamp Workplace**
- 1 x Gigabit ethernet with PoE+

Biamp MAX Connect - Media razdelnik Use
MAX app, browsers, AirPlay, Googlecast, or HDMI cable to share up to six pieces of content simultaneously
Built-in tools allow users to annotate shared content and virtual whiteboard
Shared content is rebroadcasted to the participants' devices
Participants can connect and control wirelessly any USB and HDMI room peripheral

| | |
|--------------|---|
| GENERAL | |
| Height | 1 inch (30 mm) |
| Width | 5 inches (132 mm) |
| Depth | 5 inches (132 mm) |
| Weight | 1.2 lbs (0.538 kg) |
| Mounting | Mounting plate with cable retainer (included) |
| Accessories | Bluetooth handheld remote control (included) External power supply with plug adapters (included) Touch 8 MAX LCD Control Panel (optional) |
| Kit Contents | Bluetooth handheld remote control Mounting plate with cable retainer External power supply with plug adapters |
| Warranty | 5 years |

| | |
|-----------------------|---|
| ENVIRONMENTAL | |
| Operating Environment | Temperature Range: 20° - 60° C |
| Humidity | 10% - 90% |
| POWER | |
| Power | External power adaptor 12V, 2A DC |
| Power Consumption | Standby: 0.3W (12V/110mA) Max: 7W (12V/1700mA) |
| COMPLIANCE | |
| Certifications | CB, HDMI, BQB, CE, FCC, RCM, REACH, RoHS, WEEE, CA65, SVHC233, TSCA |

The MAX Connect is an easy-to-use, yet powerful, BYOM room solution. Now participants can use their own devices to share and interact with content, control room AV equipment, and join UC meetings using their app of choice — including Microsoft Teams and Zoom. With MAX Connect, users have unprecedented control over their collaboration experience, leading to more productive meetings and enhanced engagement, ideation, and decision making.

*Biamp Launch optimizes and tunes the system to the room’s unique environment.

**Biamp Workplace compatibility is pending and will be enabled via firmware update.