

Sennheiser XSW IEM SET

Šifra: 19084

Kategorija proizvoda: In Ear Monitoring

Proizvođač: Sennheiser



Cena: 70.200,00 rsd

Transmitter

Frequency Band: A: 476 to 500 MHz

Wireless Technology: Analog, UHF

Modulation: FM Stereo

Transmitting RF Power: 30 mW

Number of RF Channels: 960

Switching Bandwidth: 24 MHz

Frequency Step Size: 25 kHz

Frequency Banks: 8 Banks with 12 Aligned and Precalculated Frequencies Each

Frequency Scanning: Manual

Max Transmitters per Band: 12

Max Operating Range: 330' / 100 m (Line of Sight)

Nominal/Peak Deviation: ± 15 kHz / ± 24 kHz

Antenna Output: BNC Socket, 50 Ohms

Frequency Response: 45 Hz to 15 kHz

Inputs: L + Mono / Right: 2 x XLR-1/4" / 6.3 mm Jack Combo Socket, Electronically Balanced

Output: 1/4" / 6.3 mm TRS, Headphones Out

Total Harmonic Distortion (THD): $< 0.9\%$

Signal-to-Noise Ratio: ≥ 88 dB, at Nominal Load and Peak Deviation

Power Input Rating: +12 VDC

Current Consumption: Approximately 400 mA

Housing: Metal

Temperature Range: 32 to 104°F / 0 to 40°C

Dimensions: Approximately 7.9 x 5 x 1.7" / 200 x 128 x 42 mm

Weight: Approximately 24.7 oz / 700 g

Receiver

Modulation: Wideband, Stereo FM

Frequency Band: A: 476 to 500 MHz

Switching Bandwidth: Up to 24 MHz

Sync Method: IR

Nominal/Peak Deviation: ± 15 kHz / ± 24 kHz

Squelch: 10 μ V, Fixed

Signal-to-Noise Ratio: ≥ 88 dB, 1 mV, Peak Deviation

Total Harmonic Distortion (THD): $\leq 1\%$

Output Level: 2 x 1.25 V_{eff} at 16 Ohms

Equalization: High Boost EQ: +10 dB at 13 kHz

Limiter: -10 dB

Frequency Response: 45 Hz to 15 kHz

Crosstalk: Typically 45 dB (50 Hz to 10 kHz)

Power Supply: 2 x AA Batteries, 1.5 V

Nominal Voltage: 3 V

Housing: Pla

stic

Operating Time: Approximately 6 Hours, Depending on Volume Level

Temperature Range: 32 to 104°F / 0 to 40°C

Dimensions: 3.7 x 2.8 x 1" / 95 x 70 x 26 mm

Weight: 3.9 oz / 110 g, Including Batteries

Earphones

Transducer: Dynamic

Frequency Response: 40 Hz to 20 kHz

SPL: 106 dB, (1 kHz, 1 mW)

Nominal Impedance: 6 Ohms

Cable Length: 4.6' / 1.4 m

Connector: 1/8" / 3.5 mm TRS, Stereo, Gold-Plated

Temperature Range: 23 to 122°F / -5 to 50°C

Packaging Info

Package Weight: 4.575 lb

Box Dimensions (LxWxH): 15.3 x 12.4 x 2.4"