Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Adam Audio D3V Black

Šifra: 19090
Kategorija prozivoda: Aktivni Studijski Monitori
Proizvođač: Adam Audio



Cena: 35.880,00 rsd

General Data
Display: Front panel multi-color LED
Cabinet Design: Dual passive radiator
Cabinet Material: PC-ABS
Mounting options: Flat on desk or loudspeaker stand (angled 15 degrees upwards on desk using supplied foot), threaded insert (3/8″) on the bottom of the cabinet for microphone stand
Power consumption (max, idle, sleep): 60 W, 5 W, 0.3 W
AC Input Voltage: 100 – 240 V, 50/60 Hz
Power Rating: 60 W max.
Operating Conditions: -10° C to +45° C (+14° F to +113° F); <70% RH, non-condensing
Weight: 3.58 kg total (7 lbs 14 oz total)
Dimensions (Height x Width x Depth): 200 mm (Height with stand: 240 mm) x 115 mm x 150 (7 7/8″” (Height with stand: 9 1/2″”) x 4 1/2″” x 5 7/8″”, 9 1/2″”)”
Warranty: 5 years (2 years warranty plus 3 years optional with product registration)
Delivery Contents: D3V primary loudspeaker, D3V secondary loudspeaker, USB-C cable with USB-A adpater, Power cable, Power block, Quick Start Guide

Audio Connectors
Analog: TRS
Input Impedance: 47 kOhm
Max. Input Level: +9 dBu
Digital: USB Type C
Digital Audio Signal: Class-compliant USB 1.1
Headphones output connector: 3.5 mm TRS mini-jack
Headphones output impedance: 32 Ohm

Amplification
Woofer
Amplifier Type: PWM
Peak (10% THD, limiter deactivated): 2 x 80 W
RMS (1% THD, limiter deactivated): 2 x 70 W
Tweeter
Amplifier Type: PWM
Peak (10% THD, limiter deactivated): 2 x 40 W
RMS (1% THD, limiter deactivated): 2 x 30 W

Control Options
Input sensitivity: 0 dBu = 88 dB SPL at 1 m @ 0 dB level setting
Level: Front panel knob controls loudspeaker and headphone outputs over the range -∞ dB to +6 dB

Front panel knob press functions: Mute, standby, input select, channel swap, firmware update mode
Input selection: Analog, USB-C
Channel order: Normal, L/R swapped
Backplate Room Adaption: Yes
Position (Bass): 0, -3, -6 dB
Desk (Low-mid and Mid): 0, -3, -6 dB and 0, -2, -4 dB
Room Acoustics (Treble): 0, -1.5, -3 dB

Acoustics
Frequency Response @ -3 dB: 48 – 22.6 kHz
Frequency Response @ -6 dB: 45 – 23.2 kHz
Crossover Frequencies: 4.0 kHz
Max SPL in full space at 1 m with sine bursts (average 100 Hz to 6 kHz) @ 3% THD (RMS): 94 dB SPL
Max SPL in full space at 1 m with sine bursts (average 100 Hz to 6 kHz) @ 3% THD (Peak): 97 dB SPL
Max SPL in full space at 1 m with sine bursts (average 50 Hz to 100 Hz) @ 3% THD (RMS): 80 dB SPL
Max SPL in full space at 1 m with sine bursts (average 50 Hz to 100 Hz) @ 3% THD (Peak): 84 dB SPL
Max peak SPL in full space at 1 m with IEC-weighted noise (full range / 80 Hz bass managed): 98 dB SPL
Dolby DARDT max SPL in full space: 103 dB SPL
Dolby DARDT max SPL in full space (bass managed): 106 dB SPL

Drivers
Woofer
Basket Diameter: 3.5″
Voice Coil Diameter: 1″ (25 mm)
Cone Material: Single-piece aluminium
Passive Radiator Basket Diameter: 2 x 3.5″
Tweeter
Type: D-ART
Diaphragm Area: 2.8 inch² (1800 mm²)
Equivalent Diaphragm Diameter: 1.9″ (48 mm)
Velocity Transform Ratio: 5 to 1
Diaphragm Weight: 0.085 g
Tweeter Dispersion: 120° horizontal, 120° vertical

Signal Processing
AD converter: 24-bit
Internal sample rate: 48 kHz
Protection: Independent peak and thermo limiters for each driver, and amplifier thermo limiters

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.