

Biamp Desono EX-S8-UB-B Black - Nazidni zvučnik

Šifra: 19129
Kategorija proizvoda: Nazidni Zvučnici
Proizvođač: Biamp



Cena: 91.080,00 rsd

Key Features

Exceptional audio clarity with small footprint and attractive styling
Uniform coverage from coaxially mounted HF/LF drivers
6-position switch selects 70 V/100 V taps or low impedance bypass
ETL listed to comply with UL 1480A, CSA 62368-1, CE marked, and RoHS compliant
EN54-24 and ISO 7240-24 certification
5-year warranty

GENERAL	
Height	18 inches (458 mm)
Width	10.2 inches (260 mm)
Depth	10.4 inches (263 mm)
Weight	24.73 lbs (11.2 kg)
Finish	RAL Color: Black RAL 9017
ENVIRONMENTAL	
Operating Environment	IP54 per IEC 60529, IEC 60068-2-5 (Solar Radiation), IEC 60068-2-11 (Salt Mist), IEC 60068-2-42 (SO ₂), IEC 60068-2-60 (Chlorine)
POWER	
Power	250W Cont. 1000W Peak

LOUDSPEAKER	
Loudspeaker Type	Two-way 8-inch surface mount loudspeaker
Operating Range	55 Hz - 20 kHz
Transformer	70V: 80W, 40W, 20W, 10W 100V: 80W, 40W, 20W
Sensitivity	(1W/1m) 90 dB
Dispersion	105° x 105°
Drivers	LF 1 x 8" HF 1 x 1.4"
AUDIO	
Impedance	8Ω
Maximum Output	115 dB 121 dB Peak
CERTIFIED SOLUTIONS	
Zoom	Zoom Certified

The Desono EX-S8 is an 8" two-way surface mount loudspeaker that provides detailed voicing with projection. It is an excellent fill or distributed loudspeaker for systems where pristine voice clarity, higher output and more bass is desired.

Designed for easy and fast installation, our innovative, patented ClickMount™ brackets provide installers with two distinct mounting options. The ClickMount pan-tilt bracket provides indexed aiming control and allows for mounting EX Series quickly in either vertical or horizontal orientation without moving the bracket position. The ClickMount U-Bracket is also available for low profile mounting or exterior use and includes the ClickPlug with an integrated gland nut for weather-resistant applications. Both brackets are theft and tamper resistant.