Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Technics SL-1300GE-K

Šifra: 19170
Kategorija prozivoda: Gramofoni
Proizvođač: Technics

Cena: 359.880,00 rsd



Key Features:
• Coreless direct drive motor with ΔΣ-Drive: provides stable and precise rotation by eliminating cogging and reducing vibration.
• Three-layer plate: combines brass, aluminum and rubber to eliminate unwanted resonances.
• High rigidity frame with double skin structure: ensures robustness and vibration damping.
• High sensitivity arm: S-shaped gimbal-mounted tonearm with high-precision bearings for accurate tracking.
• Multi-Stage Silent Power Supply: Reduces electrical noise with a low-noise switching circuit.
• Silicone insulating feet: offer excellent vibration reduction.
• High quality terminals: Gold-plated phono connectors with metal shielding to reduce external noise.
• Eco-friendly packaging materials: uses sustainable materials to reduce environmental impact.

Specifications:
Traction method: Direct drive
Motor: Brushless DC motor
Turntable speed:
• 33 1/3 rpm
• 45 rpm
• 78 rpm (Note: Actual speed at 78 rpm is 78,26 rpm)
Starting torque: 0,32 Nm (3,3 kgfcm)
Starting characteristics: 0,7 seconds from standstill to 33 1/3 rpm
braking system: Electronic brake
Oscillations and vibrations: 0,025% WRMS

Turntable platter:
• **Material:** Die-cast aluminum, brass and rubber
• **Diameter:** 332 mm
• **Weight:** Approx. 3,6kg (including rubber sheet)

Arm:
• **Type:** Static Balancing
• **Effective length:** 230 mm
• **Overhang:** 15 mm
• **Tracking error angle:**
  • Within 2°32′ (at the outer groove of a 30 cm disc)
  • Within 0°32′ (at the inner groove of a 30 cm disc)
• **Compensation angle:** 22°
• **Arm height adjustment range:** 0 – 6 mm
• **Stylus pressure adjustment range:** 0 – 4 g (direct reading)

- **Headshell Weight:** Approx. 7,6 g
- **Applicable head weight range:**
  Without auxiliary weight:
  • 5,6 – 12 g (14,3 – 20,7 g including headshell)
  With small auxiliary weight:
  • 10 – 16,4 g (18,7 – 25,1 g including headshell)
  With large auxiliary weight:
  • 14,3 – 19,8 g (23 – 28,5 g including headshell)
- **Head holder size:** 12,7mm (1/2″)
- **Headshell connection terminal:** 4 mmφ 1,2-pin terminal

Audio output terminals:
• PHONO (RCA connectors) x 1
• Grounding x 1

Supply: AC 220-240V, 50/60Hz

Energy consumption:
• 10W (operating)
• 0,3W (standby)

Dimensions (L x H x D): 453 x 173 x 372 mm

Weight: Approx. 13 kg

Operating temperature range: 0°C – +40°C

Operating humidity range: 35% – 80% RH (non-condensing)

Accessories included:
• Piatto
• Bath mats
• Dust cover
• EP Disc Adapter
• Counterweight
• Auxiliary weight
• Headshell
• Pin protrusion sensor
• Cartridge Screw Set
• PHONO cable
• PHONO grounding cable
• AC power cord
• Turntable Screw Set
• Instruction Manual

Additional notes:
• **Ecological materials:** The SL-1300G uses environmentally friendly packaging materials to reduce environmental impact, replacing styrene foam with corrugated cardboard.
• **Precision balancing:** Each platter is precision balanced at the factory to eliminate unwanted vibration and noise during rotation.

Dimensions and weight:
• Height 173mm
• Width 453mm
• Depth 372mm
• Weight: 13kg (about)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.