

Technics SL-1300GE-S

Šifra: 19171

Kategorija prozivoda: Gramofoni

Proizvođač: Technics

Cena: 359.880,00 rsd

tonearm with high-precision bearings for accurate tracking.

- Multi-Stage Silent Power Supply: Reduces electrical noise with a low-noise switching circuit.
- Silicone insulating feet: offer excellent vibration reduction.
- High quality terminals: Gold-plated phono connectors with metal shielding to reduce external noise.
- Eco-friendly packaging materials: uses sustainable materials to reduce environmental impact.

Specifications:

Traction method: Direct drive

Motor: Brushless DC motor

Turtable speed:

- 33 1/3 rpm
- 45 rpm
- 78 rpm (Note: Actual speed at 78 rpm is 78,26 rpm)

Starting torque: 0,32 Nm (3,3 kgfcm)

Starting characteristics: 0,7 seconds from standstill to 33 1/3 rpm

braking system: Electronic brake

Oscillations and vibrations: 0,025% WRMS

Turtable platter:

- **Material:** Die-cast aluminum, brass and rubber
- **Diameter:** 332 mm
- **Weight:** Approx. 3,6kg (including rubber sheet)

Arm:

- **Type:** Static Balancing
- **Effective length:** 230 mm
- **Overhang:** 15 mm
- **Tracking error angle:**
 - Within 2°32' (at the outer groove of a 30 cm disc)
 - Within 0°32' (at the inner groove of a 30 cm disc)
- **Compensation angle:** 22°
- **Arm height adjustment range:** 0 – 6 mm
- **Stylus pressure adjustment range:** 0 – 4 g (direct reading)
- **Headshell Weight:** Approx. 7,6 g

- **Applicable head weight range:**
Without auxiliary weight:
 - 5,6 – 12 g (14,3 – 20,7 g including headshell)With small auxiliary weight:
 - 10 – 16,4 g (18,7 – 25,1 g including headshell)With large auxiliary weight:
 - 14,3 – 19,8 g (23 – 28,5 g including headshell)

- **Head holder size:** 12,7mm (1/2")

Technics SL-1300GE-S

- **Headshell connection terminal:** 4 mmφ 1,2-pin terminal

Audio output terminals:

- PHONO (RCA connectors) x 1
- Grounding x 1

Supply: AC 220-240V, 50/60Hz**Energy consumption:**

- 10W (operating)
- 0,3W (standby)

Dimensions (L x H x D): 453 x 173 x 372 mm**Weight:** Approx. 13 kg**Operating temperature range:** 0°C - +40°C**Operating humidity range:** 35% - 80% RH (non-condensing)**Accessories included:**

- Piatto
- Bath mats
- Dust cover
- EP Disc Adapter
- Counterweight
- Auxiliary weight
- Headshell
- Pin protrusion sensor
- Cartridge Screw Set
- PHONO cable
- PHONO grounding cable
- AC power cord
- Turntable Screw Set
- Instruction Manual

Additional notes:

- **Ecological materials:** The SL-1300G uses environmentally friendly packaging materials to reduce environmental impact, replacing styrene foam with corrugated cardboard.
- **Precision balancing:** Each platter is precision balanced at the factory to eliminate unwanted vibration and noise during rotation.

Dimensions and weight:

- Height 173mm
- Width 453mm
- Depth 372mm
- Weight: 13kg (about)