logo not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

Thechnics Std 1300 Star Snown

Key

# Technics SL-1300GE-S

Šifra: 19171

Kategorija prozivoda: Gramofoni

Proizvođač: Technics

Cena: 359,880.00 rsd

#### Features:

- Coreless direct drive motor with ΔΣ-Drive: provides stable and precise rotation by eliminating cogging and reducing vibration.
- Three-layer plate: combines brass, aluminum and rubber to eliminate unwanted resonances.
- High rigidity frame with double skin structure: ensures robustness and vibration damping.
- High sensitivity arm: S-shaped gimbal-mounted

tonearm with high-precision bearings for accurate tracking.

- Multi-Stage Silent Power Supply: Reduces electrical noise with a low-noise switching circuit.
- Silicone insulating feet: offer excellent vibration reduction.
- High quality terminals: Gold-plated phono connectors with metal shielding to reduce external noise.
- Eco-friendly packaging materials: uses sustainable materials to reduce environmental impact.

## **Specifications:**

Traction method: Direct drive Motor: Brushless DC motor

#### **Turntable speed:**

- 33 1/3 rpm
- 45 rpm

• 78 rpm (Note: Actual speed at 78 rpm is 78,26 rpm)

**Starting torque:** 0,32 Nm (3,3 kgfcm)

Starting characteristics: 0,7 seconds from standstill to 33 1/3 rpm

braking system: Electronic brake

Oscillations and vibrations: 0,025% WRMS

#### **Turntable platter:**

• Material: Die-cast aluminum, brass and rubber

• Diameter: 332 mm

• Weight: Approx. 3,6kg (including rubber sheet)

• Type: Static Balancing • Effective length: 230 mm

• Overhang: 15 mm

• Tracking error angle:

• Within 2°32′ (at the outer groove of a 30 cm disc) Within 0°32′ (at the inner groove of a 30 cm disc)

• Compensation angle: 22°

• Arm height adjustment range: 0 - 6 mm

• Stylus pressure adjustment range: 0 - 4 g (direct reading)

• Headshell Weight: Approx. 7,6 g

Applicable head weight range:

Without auxiliary weight:

• 5,6 - 12 g (14,3 - 20,7 g including headshell)

With small auxiliary weight:

• 10 - 16,4 g (18,7 - 25,1 g including headshell)

With large auxiliary weight:

• 14,3 - 19,8 g (23 - 28,5 g including headshell)

• **Head holder size:** 12,7mm (1/2")

• Headshell connection terminal: 4 mmφ 1,2-pin terminal

### **Audio output terminals:**

- PHONO (RCA connectors) x 1
- Grounding x 1

**Supply:** AC 220-240V, 50/60Hz

# **Energy consumption:**

- 10W (operating)
- 0,3W (standby)

**Dimensions (L x H x D):** 453 x 173 x 372 mm

Weight: Approx. 13 kg

**Operating temperature range:** 0°C - +40°C

Operating humidity range: 35% - 80% RH (non-condensing)

#### **Accessories included:**

- Piatto
- Bath mats
- Dust cover
- EP Disc Adapter
- Counterweight
- Auxiliary weight
- Headshell
- Pin protrusion sensor
- Cartridge Screw Set
- PHONO cable
- PHONO grounding cable
- AC power cord
- Turntable Screw Set
- Instruction Manual

#### Additional notes:

- **Ecological materials:** The SL-1300G uses environmentally friendly packaging materials to reduce environmental impact, replacing styrene foam with corrugated cardboard.
- **Precision balancing:** Each platter is precision balanced at the factory to eliminate unwanted vibration and noise during rotation.

## **Dimensions and weight:**

- Height 173mm
- Width 453mm
- Depth 372mm
- Weight: 13kg (about)