Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Audient ORIA



Šifra: 19182
Kategorija prozivoda: USB Zvučne kartice
Proizvođač: Audient

Cena: 200.027,00 rsd

Hardware Features:
• Supports up to 9.1.6 Speaker Setups
• 2 x 16 Channel Surround Outputs (Analogue & AES)
• 2 x Stereo Line Outputs (Relay Switched)
• 2 x Independent Stereo Headphone Outputs
• 2 x Audient Mic Preamps (Mic / D.I / Line)
• 2 x ADAT Inputs
• Word Clock Input
• Word Clock Output
• ORIA Motion UI
• 24 bit / 96kHz
• USB 2.0 / USB Type-C
• Sonarworks SoundID Reference Measurement Microphone Included
• Optional AoIP Card (Dante) for 16 Input channels

Software Features:
Immersive Monitoring Control
• Input / Output Switching
• Master Volume Control
• Global Delay (lip sync)
• Individual Speaker Solo & Mute
• Speaker Group Solo & Mute
• Per Channel Metering (pre & post)
• Down Mix Cycling – Dolby Renderer Integrated
• Programmable Function Button

iPad Control App
Onboard Room Calibration DSP
• Per Output EQ
• Per Output Delay
• Per Output Trim
• Per Output Crossover (Bass Management)
• Profile Switching – Sonarworks Integrated
• Configurable Global Bypass

Microphone Inputs
Gain: 60dB
Max Input Level: +18dBu
Crosstalk: <105dB

THD+N: 0.0015% / -96dB
EIN: -129dB
CMRR: -85dB
SNR: 100dB
Frequency Response: ±0.5dB 20Hz to 40kHz
Input Impedance: 1.5kΩ Balanced

Line Inputs
Gain: -10dB to +50dB
Max Input Level: +18dBu
THD+N: 0.0015% / -96dB
Input Impedance: 4.7kΩ Balanced
D.I / Instrument Input
Gain: 60dB
Max Input Level: +18dBu
THD+N: 0.16%
SNR: 100dB
Frequency Response: ±0.5dB 20Hz to 40kHz
Input Impedance: 370kΩ Unbalanced

Line Outputs
Lineup Level: +18dBu
THD+N: 0.0006%, -105dB
Dynamic Range: 126.5dB
Crosstalk: -123dB
Frequency Response: ±0.3dB 10Hz to 40kHz
Output Impedance: <100Ω Balanced

Headphone Outputs
Lineup Level: +18dBu
THD+N: 0.0007% (-103dB)
Dynamic Range: 124dB
Crosstalk: -115dB
Frequency Response: ±0.25dB 10Hz to 40kHz
Output Impedance: <50 Ω Unbalanced
Max Level @ 30R: 5.47V Peak, 3.87Vrms, 997mW
Max Level @ 60R: 7.4V Peak, 5.29Vrms, 912mW
Max Level @ 600R: 8.6V Peak, 6.09Vrms, 123mW

USB-C
Connector: USB Type C
Included Cable: USB Type-C to Type-C
Number of Input Channels: 34 (2x Analogue, 16 Digital, 16 AOIP*)
Number of Output Channels: 38 (20 Line Outs, 2x Stereo Headphone Outs, 16x AES)
*With AOIP card fitted

Digital Inputs
ADAT 16 Channels: 44.1kHz to 48kHz
ADAT 8 Channels (SMUX): 88.2kHz to 96kHz

Digital Outputs
AES Outputs: 16 Audio Channels (8x AES Data Streams)

Word Clock Input and Output
Word Clock: 44.1kHz to 96kHz

DSP Latency
Round Trip:
• 44.1kHz – 6.5ms
• 48kHz – 6.3ms
• 88.2kHz – 5.5ms

• 96kHz – 5.4ms

AOIP (Optional Dante Expansion Card)
AOIP Inputs: 16 (44.1kHz to 96kHz)

Power Supply
Input Voltage: 85 – 264 VAC
Input Frequency: 47 – 63Hz

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.