

Zoom H1 XLR

Šifra: 19361

Kategorija proizvoda: Snimači/Rekorderi

Proizvođač: ZOOM

Cena: 19.080,00 rsd



INPUTS

MIC/LINE (mono)

- Connectors: 2 XLR/TRS combo jacks (XLR: 2 HOT, TRS: TIP HOT)
- Input gain: Adjustment unnecessary (dual A/D converter circuits used)
- Input impedance: MIC: 2.7 k Ω or more

LINE: 1 k Ω or more

- Maximum input level: MIC: +4 dBu

LINE: +24 dBu

- Phantom power: +48 V

Channel total 10 mA or less

- Equivalent input noise: MIC: -122 dBu or less (IHF-A) at 150 Ω input

LINE: -100 dBu or less (IHF-A) at 600 Ω input

MIC/LINE IN jack

- Connector: Stereo mini jack
- Input impedance: 2 k Ω
- Plug-in power: 2.5 V

OUTPUTS

PHONE / LINE OUT jack

- Connector: Stereo mini jack
- Maximum output level: 20 mW + 20 mW (when 32 Ω load)
- Output impedance: 10 Ω or less

Built-in speaker

- Type: 20 mm x 30 mm elliptical dynamic speaker
- Effective maximum output: 250mW

RECORDER

- Recording format: WAV
44.1, 48 or 96 kHz / 32-bit float

Stereo / Mono

BWF and iXML formats supported

- Recording media: 4 - 32GB cards compatible with the microSDHC specification
64GB - 1TB cards compatible with the microSDXC specification

DISPLAY

- OLED: 128 x 64

USB

- Connector: USB Type-C

- Use a USB cable that supports data transfer.
- Audio interface: USB Audio Class 1.0
- Input and output channels: 2 in / 2 out (Stereo)
- Sampling frequencies: 44.1, 48 kHz
- Bit depths: 16-bit, 32-bit float
- File transfer: USB 2.0 High Speed

POWER

- 2 AA batteries: Alkaline, Lithium, or Rechargeable NiMH
- AC adapter: ZOOM AD-17: DC 5 V/1 A
- USB bus power is supported.