

Citronic CSP-408

Šifra: 19543

Kategorija proizvoda: Miksete sa Snagom

Proizvođač: Citronic

Cena: 39.480,00 rsd



Powered mixer with balanced mic/line inputs and 2 stereo inputs, each with 3-band EQ and aux send. A 16 program DSP section with tap tempo can provide vocal effects and a 7-band graphic EQ facilitates global tone control. The built-in stereo amplifier delivers ample power to drive 2 or 4 speakers for coverage in medium sized venues, offering a compact and comprehensive solution for mobile PA, bars and special events.

- 24-bit 16 program DSP effects
- 48V phantom power for XLR inputs
- 3-band EQ per channel
- 7-band global graphic EQ
- Internal stereo power amplifier
- Balanced main outputs

- Weight 6.80kg
- Dimensions 315 x 322 x 153mm
- Inputs : Mic/Line 4 x balanced XLR/TRS jack
- Output power : 8 Ohms 2 x 130Wrms
- Output power @ 4 Ohms 2 x 200Wrms
- Fuse T10A (5 x 20mm, 250V)
- Power consumption 600W
- Power supply 230Vac 50Hz (IEC)
- Speaker : outputs L+R SPK connectors
- Effects 16 program DSP (24-bit sigma-delta, 40kHz)
- Phantom power +48V (XLR inputs)
- Frequency response 20Hz-30kHz (0.5dB)
- Input level +24dBu
- Output level : line +26dBu
- CMRR >74dB (mic 1kHz)
- THD +N <0.01% (channel to main out)
- Crosstalk >85dB (fader mute), >82dB (channel)
- Noise rms : 22Hz-22kHz -122dBu (EIN), -82dBu (mix)
- EQ: high 12kHz ±15dB shelving
- EQ: mid 2.5kHz ±15dB band pass
- EQ: low 80Hz ±15dB shelving
- Input impedance : mic (balanced) 2k Ohms
- Input impedance : line (balanced) 10k Ohms
- Sensitivity : mic -60 to +14dBu
- Sensitivity : line -40 to +14dBu
- 2-track 2 x RCA in & out (-2dBu)

Output impedance <75 Ohms
Headphone output 6.3mm jack, 30-600 Ohms