1090e not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

Citronic Neolith mk2 Active Sub + Column Array

Šifra: 19544

Kategorija prozivoda: Aktivne Zvučne Kutije

Proizvođač: Citronic

Cena: 68.280,00 rsd

Gittonic Neolithmk2 Active Sub + Column Array

Neolith is a self-contained active sub & column speaker system that delivers superb sound quality for medium to high volume PA applications. Maintaining a minimal footprint, the compact sub cabinet is loaded with a high power 10" low frequency driver, and is also home to the powerful class-D bi-amp module. For mid and high frequency reproduction, the column speaker has a quartet of high power full-range drivers, which have Neodymium magnets to maximise response and efficiency at these frequencies. Sub and column are

assembled using a specially-designed mounting pole, which also serves to connect the column speakers to the amplifier output. This makes setting up and breaking down a matter of seconds for mobile work. The amplifier is also governed by a DSP circuit, offering 5 distinct tonal profiles that may be selected for different sound duties. Two input channels can each accept a line input with one switchable to Mic level, with the other also serving as an input for the inbuilt Bluetooth receiver. Convenience and ease of use are the key benefits of Neolith, providing power and great sound quality without fuss or frustration.

Neodymium full-range drivers Self-contained active PA system Built-in Bluetooth receiver Speaker connection integral to mounting pole

Finish Black polyurea coating Power supply 230Vac, 50Hz (IEC) Fuse T3.15AL 250V (5 x 20mm)

Construction 15mm MDF with texture polyurea coating

Output power : rms 400W Output power : max. 800W

Audio source Internal Bluetooth receiver

Inputs Mic/Line(XLR/Jack) and Line (Jack/RCA)

DSP settings 5 x preset tone profiles

Output Line out (XLR)

Sub driver 1 x 250mmØ (10")

Column drivers 4 x 90mmØ (3.5") Neodymium

Sensitivity 94dB

Frequency response 55Hz - 20kHz

Height 1.72m (assembled)

Dimensions: sub cabinet 450 x 400 x 320mm

Weight: sub cabinet 15.95kg

Dimensions: column 520 x 143 x 111mm

Weight: column 2.95kg

In the Box

10" active sub cabinet4 x 3.5" satellite column array