

## CARVIN DCM 2570

Šifra: 2356  
Kategorija proizvoda: Razglasna Pojačala  
Proizvođač: CARVIN

Cena: **107.880,00** rsd

### DCM2570 - 2400W at 8 ohms Power Amp

Pristine sound, brute power and no-fault reliability make the DCM amps the power amp of choice for professionals. Designed for continuous operation, overheating is not a problem. Massive Toroid power supplies with huge capacitors deliver the bass that kick drums demand - you will feel the deep, resonating power that other amps lack.

Mechanically the DCM's are superior to the imports that are so prevalent today. Each DCM is hand built at our San Diego factory featuring all steel construction, recessed controls and heavy-duty power components. Soft-start relays gently turn the DCM's on so when you plug into a 15 amp breaker it won't trip. The DCM is the only amp that offers the connectivity of 1/4 TRS & XLR inputs along with 1/4", binding post and Neutrik Speakon outputs on most models. The rock-solid, efficient design with its superb, testimonial-proven sound, makes the USA built DCM an amp you'll gladly own for years.

### DCM2570 Power Amp SPEC.

<b>Bridged RMS Continuous</b> 8Ω, (20-20k Hz, <1.0%):	2400W
<b>Both Channels RMS Continuous</b> 4Ω (20-20k Hz, <1.0%):	1200W/1200W
8Ω (20-20k Hz, <1.0%):	700W/700W
<b>THD (20-20k Hz 50% power)</b>	0.03%
<b>THD (20-20k Hz 90% power)</b>	0.1%
<b>Damping Factor:</b>	>500
<b>Slew Rate:</b>	bridged mode >50v/μs
<b>Sensitivity:</b>	(4Ω, Vrms) 1.0 V
<b>Signal to Noise Ratio:</b>	Above 100dB
<b>Frequency Response:</b>	±0.5 dB, 20 Hz to 20kHz
<b>Input Impedance:</b>	(±1.5 dB, 10 Hz & 40 kHz) >20K Ω, balanced
<b>Protection Circuits:</b>	Short Circuit • No Load Protection • SpeakerGuard™ • Thermal Shut-Off • Mute On/Off

	<b>Front:</b> Power switch • Recessed detente attenuators • Signal LED • Clip LED • Protect LED • Power Indicator
<b>Internal Fuse SLOW BLOW</b>	<b>Rear:</b> Ground Lift (each channel) • Parallel Input Switch • Speaker Output 25A 240V/15A Bridge Switch • Limiters
<b>Dimensions:</b>	5 1/4" High x 19" Wide x 10" Depth (3-space); 13.3 x 48.3 x 25.3 cm
<b>Net Weight:</b>	IN/OUT Switch • Input Connectors: Two each, Balanced XLR & 1/4" Speaker Output Connectors: 39 lbs (16.7Kgs)
<b>Control and Indicators:</b>	Dual heavy duty binding posts, three Speakon™ & four 1/4"