

ELEKTRON Analog Four MKII

Šifra: 19715

Kategorija proizvoda: Sound Moduli

Proizvođač: ELEKTRON

Cena: 194.280,00 rsd



Specifications

Synth voice features (×4)

Fully analog signal path

2 × analog oscillators

Variable waveshape on all waveforms

Oscillator AM and sync modes

2 × sub-oscillators

1 × noise generator

1 × 4-pole analog lowpass ladder filter

1 × 2-pole analog multi-mode filter

1 × analog overdrive circuit Filter feedback

2 × assignable LFOs

1 × dedicated vibrato LFO

2 × dedicated waveshape LFOs

1 × amp envelope

2 × assignable envelopes

2 × dedicated LFO fade envelopes

1 × dedicated noise fade envelope

1 × dedicated vibrato envelope

1 × dedicated autobend envelope

3 × individual send effects

Polyphony

Up to 4 notes of polyphony

Up to 4 part multitimbrality

Up to 4 note unison playback

Storage

128 projects

4096 sounds (+Drive sound library)

128 sounds per project (project sound pool)

128 kits per project

128 patterns per project

16 songs per project

Sequencer

4 synth tracks

1 FX track

1 CV/Gate track

Sequencer MIDI Out

Up to 64 steps per pattern

Individual length per track

Individual scale per track

6 × arpeggiators

Parameter locks

Step recording mode

Trig preview

Trig probability

Instant pattern, kit, and sound reload

Live friendly performance mode

Swing, slide, accent

Track transpose

Micro timing

Sound-per-step change

Full real-time control

Send effects

Chorus

Delay

Reverb

Hardware

128 × 64 pixel OLED screen

MIDI In/Out/Thru with DIN Sync out

2 × 1/4" impedance balanced main audio out jacks

4 × 1/4" separate stereo voice output jacks

2 × 1/4" audio in jacks

1 × 1/4" stereo headphone jack

4 × 1/4" CV/Gate outputs

2 × 1/4" CV/Expression inputs

48 kHz, 24-bit D/A and A/D converters

USB 2.0 Hi-Speed port

Balanced audio outputs

Headphones out level: +19 dBu (55 Ω)

Main outputs level: +19 dBu

Output impedance: 440 Ω unbalance

Unbalanced external inputs

Input level: +19 dBu maximum

Audio input impedance: 9 kΩ

CV/Expression inputs

Input voltage on tip: -5 V - +5 V. Supplies +5 V on ring

Accepts CV, expression pedals

CV outputs

Voltage range:-10 V--+10 V.

Digital S/N ratio: 102 dBFS (20-20.000 Hz)

Electrical specifications

Unit power consumption: 15 W typical, 20 W maximum

Recommended power supply: 12 V DC, 2 A

Physical specifications

Aluminum enclosure

Dimensions: W385 × D225 × H82 mm (15.2 × 8.85 × 3.3") (including knobs, jacks, and feet)

Weight: approximately 2.4 kg (5.3 lbs)

Miscellaneous

Overbridge enabled

Class compliant USB audio

3 year Elektron warranty

Included in the box

Power Supply PSU-3c

Elektron USB cable

Quick Guide