

Eversolo DMP-A6 Master Edition Gen 2 Silver

Šifra: 19807

Kategorija proizvoda: Network Plejeri

Proizvođač: Eversolo



Cena: 155.880,00 rsd

Basic Parameters

Model: EVERSULO DMP-A6 Master Edition Gen 2

Display: 6-inch LCD Touchscreen

Internal Memory: 4GDDR4 +32G eMMC

DAC: ES 9038Q2M*2

Audio Processor: XMOS XU316

Op-amp Chip: OPA1612

Power Supply: Low Noise, High-Quality Linear Power Supply

Built-in SSD Slot: M.2 NVME 3.0 2280 Interface Protocol, Supports up to 8TB

USB-A Ports: USB3.0*2

Ethernet: RJ-45 (10/100/1000Mbps)

Wireless Network: WiFi 2.4G+5G Dual-Band

Music Playback and DAC Decoding: Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format

Music Services: TIDAL, Qobuz, HIGHRESAUDIO, Amazon Music, IDAGIO, Calm Radio, Internet Radio, TuneIn, Radio Paradise, Deezer, SoundCloud, Presto Music, Apple Music*...

Network Protocol: WebDAV, UPnP, NFS, SMB, Onedrive, Drop box, emby, Plex...

Streaming: Roon Ready, DLNA, TIDAL Connect...

Control Methods: Mobile App Control, Touchscreen Control, Tablet App Control, TRIGGER OUT, WOL

Audio Input and Output

Bluetooth Audio Input: Bluetooth BT5.0, Supports SBC/AAC

USB-B Audio Input:

- USB Audio Compatibility: Windows (10, 11), Mac, Android, iOS
- Supports up to Stereo DSD512, PCM 768KHz 32Bit, MQA Format

Optical/Coaxial Audio Input: Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format

HDMI ARC Input: Supports up to Stereo PCM 192KHz/24Bit

USB Audio Output: Supports up to Stereo DSD512 Native, PCM 768KHz 32Bit, MQA Format

HDMI Audio Output: DSD64 Native multichannel/PCM 192KHz multichannel raw output, up to 5.1

Optical/Coaxial Audio Output: Supports up to Stereo PCM 192KHz 24Bit, Dop64, MQA Format

Analog Audio Output: Pre-output: XLR (Balanced) + RCA(UnBalanced)

Audio Characteristics

XLR Output Audio Characteristics:

- Output Level: 5.2V
- Frequency Response: 20Hz~20KHz (± 0.15 dB)
- Dynamic Range: >128dB
- SNR: >128dB @A-wt

- THD+N: <0.000087%(-121dB)

- Crosstalk: >-125dB

RCA Output Audio Characteristics:

- Output Level: 2.6V

- Frequency Response: 20Hz~20KHz (± 0.2 dB)

- Dynamic Range: >125dB

- SNR: >125dB @A-wt

- THD+N: <0.0001%(-120dB)

- Crosstalk: >-124dB

Other Information

PSU: AC 110~240V 50/60Hz Max 0.35A

Rated Power: 13W

Dimensions: L 187mm * W 270mm * H 90mm

Packing List: Power Cable*1, USB Data Cable*1, Trigger Cable*1, User Manual*1

Color: black / silver