

logo not found or type unknown

Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Biamp Desono DP6-B Black

Šifra: 19848
Kategorija proizvoda: Viseći Zvučnici
Proizvođač: Biamp

Cena: 53.880,00 rsd

- Tru-Phase high-frequency waveguide
- Patented Carbon Ring Cone Technology
- High efficiency, high output, high intelligibility, low distortion
- Paintable enclosure constructed of high-impact ABS plastic to reduce resonances
- Easy-access power tap switch for selectable 8 ohm or 70V/100V operation
- Integrated rear cover hiding all wires and hanging hardware
- Weather-resistant constructed with treated drivers and two-layer powder coated grilles
- ETL listed to comply with UL1480
- Available in standard black or white finishes
- 5-year warranty

Biamp Desono DP6-B Black

Key

Features

- Zoom Rooms Certified
- Stylish, contoured contemporary pendant design
- Same components and voicing as the DX ceiling and surface mount loudspeaker family
- Consistent, wide dispersion up to 16 kHz
- True coaxial loudspeakers with HF compression drivers

GENERAL	
Height	14.73 inches (374.2 mm) high enclosure
Width	11.22 inches (285 mm) face diameter
Weight	11.8 lbs (5.4 kg)
Finish	Black
Material	Grille: Powder coated steel with safety line, black or white finish, paintable
Enclosure	Baffle: Reflex loaded UL 94V-0 rated ABS
Mounting	Two PHK-15 pendant hang kits (one for main suspension and one as a safety cable), each including 15ft (4.5m) long 2mm (0.77 inch) high tensile galvanized steel wire rope suspension cables with integrated spring clips for attaching the cable to the loudspeaker bracket and Gripple™ brand adjustable height cable fasteners.

Included Accessories	<p>Included Accessories:</p> <p>Two PHK-15 pendant hang kits</p> <p>Enclosure ABS plastic rear cover</p> <p>Rear cover ingress weather plug</p> <p>Optional Accessories:</p> <p>PHK-30 30ft (9.1m) pendant hang kit</p> <p>PHK-50 50ft (15.2m) pendant hang kit</p> <p>PSC replacement Gripple™ speed clamp</p> <p>PST-14 trimmable 14ft (4.3m) decorative split loom tubing</p>
Required Accessories	Electronic high pass filter
CONTROLS & INDICATORS	
Control	Front-face wattage / low impedance selector switch
AMPLIFIER	
Distortion	<p>Distortion - 10% Full Power:</p> <p>2nd Harmonic</p> <p>500 Hz: 1.74%</p> <p>2 kHz: 1.18%</p> <p>8 kHz: 0.77%</p> <p>3rd Harmonic</p> <p>500 Hz: 1.19%</p> <p>2 kHz: 0.35%</p> <p>8 kHz: 0.04%</p>
LOUDSPEAKER	
Loudspeaker Type	Two-way, full-range, coaxial pendant mount loudspeaker, 8 ohm or 70V/100V operation
Operating Range	65 Hz - 22 kHz
Crossover	Crossover Frequency: 1.2 kHz
Transformer	<p>Transformer Taps</p> <p>70V: 60W, 30W, 15W, 7.5W and low impedance</p> <p>100V: 60W, 30W, 15W</p>
Sensitivity	<p>(1W/1m): 94 dB SPL (125 Hz to 12.5 kHz 1/3 octave bands)</p> <p>92 dB SPL (250 Hz to 4 kHz speech range)</p>
Coverage	<p>Nominal Coverage: 115º conical (1 kHz to 6 kHz)</p> <p>125º conical (500 Hz to 6 kHz)</p>

Signal Processing	Recommended Signal Processing: 65 Hz high pass filter
Drivers	LF 1 x 6.5-inch HF 1 x 1-inch exit compression driver Driver Protection: Self-resetting solid state circuit breaker
AUDIO	
Input Type	Input Connection: Two 2-position Euroblock connectors
Impedance	Nominal Impedance: 8 ohms Minimum Impedance: 6.9 ohms @ 210 Hz
Maximum Input	100W continuous, 250W program 28 volts RMS, 63 volts momentary peak
Maximum Output	114 dB SPL / 120 dB SPL (peak 8 ohm)
Frequency Response	80 Hz - 20 kHz (± 5 dB)
CERTIFIED SOLUTIONS	
Zoom	Zoom Certified
COMPLIANCE	
Safety Features	Safety Features: Included safety cable. Each cable has an SWL of 99 lbs (45 kg). Safety Agency Ratings: EETL listed to comply with UL1480 and CSA60065. Suspension system and Gripple™ brand cable fastener listed per UL1598 and UL2239, TUV and CSA Class 3426-01 and Class 3426-81.
NOTES	
Specification Notes	Axial Q / DI: 4.7 / 6.7, 500 Hz to 6 kHz