

TANNOY Definition DC8

TANNOY Definition DC8

Šifra: 10433
 Kategorija proizvoda: Bookshelf Zvučnici
 Proizvođač: Tannoy

Cena: 119.880,00 rsd

A purist Tannoy loudspeaker the Definition DC8 is a bold stand mount design of beautiful proportions. The DC8 offers the latest 8 inch Dual Concentric™ drive unit in a compact, curve wall cabinet constructed from the finest plywood. The 25mm titanium dome tweeter with tulip waveguide is a true WideBand™ design and offers exceptional high frequency extension while the powerful bass driver and 19 litre port tuned enclosure offers class leading bass down to almost 40Hz. The treated paper pulp mid-bass cone had a rubber surround and 44mm edge wound voice coil for extremely high efficiency and high power handling.

Inside the formidable definition DC8, the crossover uses audiophile grade components throughout in a design hand build and set in DMT onto non-resonant boards. Wiring is silver plated 99.99% pure copper for the mid-bass and incoming signal, while the HF section is wired in high purity solid silver cabling. The terminal panel is furnished with five WBT gold plated binding posts allowing single or bi-wiring and the use of Tannoy's unique fifth terminal to ground the driver chassis. Deep Cryogenic treatment of the entire crossover and extensive use of Tannoy DMT™ technology further improves resolution of detailing and microdynamics.

On the outside the Definition DC8 exudes class and style from the deep lustre gloss lacquer over real wood veneer or piano black, to the flush fitting trim and seemingly fixingless magnetic grille mounts. Whether used as high fidelity monitors in an audiophile music system or as part of a high-end multichannel music and movie set-up, the Definition DC8 delivers unsurpassed accuracy and articulation. The high-class, high-tech Definition DC8 is Tannoy's flagship stand mount loudspeaker.

Specifications

PERFORMANCE	
Recommended amplifier power (Watts RMS)	30 - 175
Continuous power handling (Watts RMS)	87
Peak power handling (Watts)	350
Sensitivity (2.83 Volts @ 1m)	88 dB
Nominal Impedance (Ohms)	8
Frequency response (-6 dB)	42 Hz - 35 kHz
Dispersion (degrees conical)	90
DRIVE UNITS	
Dual Concentric™ high frequency	25 mm (1") Titanium dome with Tulip Waveguide™

Dual Concentric™ low frequency	200 mm (8") treated paper pulp cone with rubber surround. 44 mm (1.75") edge wound voice coil
CROSSOVER	
Crossover frequency	1.5 kHz
Crossover type	Passive low loss 2nd order LF, 1st order HF Deep Cryogenically Treated
CONSTRUCTION	
Enclosure Type	Rear ported
Volume	19 L (0.67 cu. ft.)
Dimensions (H x W x D) excl grille	470 x 271 x 260 mm (18.5 x 10.7 x 10.2")
Weight	10 kg (22.05 lbs)
Finish	High gloss black High gloss cherry High gloss dark walnut