Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

SYNQ DBT 44

Šifra: 19920
Kategorija prozivoda: Proširenja
Proizvođač: SYNQ



Cena: 113.880,00 rsd

Premium quality analog / Dante network audio bridge for touring.
Converts DANTE® and/or AES67 network audio to 4 hi-grade balanced analog outputs.
Converts 4 hi-grade balanced analog inputs to DANTE® and/or AES67 Network audio.
All 4 (LINE/MIC) inputs equipped with -24dB PAD & 48V Phantom power.
GIGABIT Ethernet I/O based on Hi-speed Marvell switch (no linking delays).
Built-in DSP AUDIO PROCESSING (parametric EQs, compressors, delays, ...) on all channels: perfect for use as DANTE enabled speaker management processor, but also deployable in many other applications.
8x8 AUDIO MATRIX for local premix, flexible routing, ...
Integrated WEB SERVER: fully graphical and very user-friendly user interface for easy configuration and DSP control on any network device!
The included “SYNQ Network Discovery Tool” software makes it extremely easy to find the device(s) on a local network and open them on any desktop computer, without any knowledge of the IP-address.
Support for the OSC protocol: all functions can be controlled by user-created apps running on iPhones, Android phones, Tablets and desktop computers.
Extremely high audio quality: S/N > 120dB ~ THD: < 0.003%
Fully equipped with original Neutrik® XLR and EtherCON connectors.
Complies with IEEE 802.3-2005 standard for Information Technology.
Extreme reliability, thanks to the exclusive use of industrial-grade components, such as: high-end Burr Brown audio DACs, AKM ADCs, Wurth electrolytic capacitors, ...
POWER options:
PowerCON TRUE1: 100-240Vac 50/60Hz
PoE: Power over Ethernet (PoE class 0)
HOUSING: ½ 19” diecast housing with different installation options:
1 unit fits in a 1U 19" rack (19" adapter included)
2 units fit together in a 1U 19" rack (adapters included)
Easy wall mounting with optional wall mount adapter
Easy truss mounting with optional truss mount adapter

General : Dimensions (cm)	22 x 20.5 x 4.4
General : Weight (kg)	1.35
General : Color	black

General : Energy Label	No
General : Display	No
General : Fixation	19" rack mountable
General : RU	1U
General : IP rating	indoor
Control : Protocol	DANTE, AES67
Audio : functions	equalizer, adjustable crossover, DSP, limiter
Connections : input	3 pin XLR, jack, PowerCon® TRUE1 or compatible
Connections : output	3 pin XLR, PowerCon® TRUE1 or compatible

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.