

Audiolab 9000Q Silver - Pretpojačalo

Šifra: 19993

Kategorija proizvoda: Pretpojačala

Proizvođač: Audiolab



Cena: 194.292,00 rsd

Model: 90000Q

General Description: Preamplifier

Design Philosophy and Core Technology:

- ES9038Pro 32-bit DAC
- MQA Full decoder (PC USB, Coax/Optical)
- 4.3" 800 x 480 IPS LCD
- Bluetooth 5.1 (aptX/aptX HD/LDAC) streaming
- Dedicated Current-Feedback Headphone Amp
- Dedicated High Performance Low Noise MM Phono stage

Inputs:

- 3 x Analogue, 1 x XLR, 1 x Phono (MM)
- 2 x SPDIF (Coax), 2 x SPDIF (Optical)
- 1 x PC USB (USB B), 1 x Bluetooth (aptX/aptX HD/LDAC)

Outputs: 2 x RCA, 1 x XLR, 1 x Headphone, 2 x 12V Trigger

Sampling Frequency:

- Optical/Coaxial: 44.1-192kHz
- Sampling Frequency
- PC USB: 44.1kHz-768kHz (PCM) / DSD64, DSD128, DSD256, DSD5, DSD512

Preamp / DAC

D to A Converter: ES9038Pro

Input Sensitivity:

- 1Vrms (Line, Volume = 0dB)
- 2Vrms (XLR, Volume = 0dB)
- 4.5mV (Phono MM, Volume = 0dB)

Total Harmonic Distortion (THD): < 0.001% (1KHz @ 0dBFS)

Frequency Response: 20Hz - 20kHz (+/-0.1dB)

Output Impedance: 120 ohm

Max.Sampling Frequency:

- Optical, Coaxial: 192KHz
- PC USB: PCM768kHz, DSD512

Signal-to-noise Ratio (S/N):

- > 113dB (A-weighted, RCA)
- > 117dB (A-weighted, XLR Direct)

Headphone Amplifier

Total Harmonic Distortion (THD): < 0.01% (1kHz, 50mW)

Output Impedance: 2.35 ohm

Load Impedance: 20-600 ohm

General**Standby Power Consumption:** <0.5W**Net Weight:** 6.2kg**Gross Weight:** 8kg**Dimensions(mm) (W x H x D):** 444 x 90 x 328 mm**Carton Size (mm) (W x H x D):** 514 x 165 x 470 mm**Finish:** Silver / Black**Power Requirements(depending on region):**

- 220-240V - 50/60Hz
- 100-120V - 50/60Hz

Standard Accessories: Power Cord, Remote Control, User Manual, Antennas