

Audiolab D9 Black - DAC

Šifra: 19987

Kategorija proizvoda: DAC-ovi

Proizvođač: Audiolab



Cena: 140.292,00 rsd

Model: D9

General Description: DAC

Design Philosophy and Core Technology:

- ES9038Pro 32-bit DAC
- MQA Full decoder (PC USB, Coax / Optical)
- 2.8" 480x640 large size full view IPS LCD
- Bluetooth 5.1 (aptX / aptX HD / LDAC) streaming
- Dedicated Current-Feedback Headphone Amp
- VU Digital / VU Analogue Meter
- USB HDD Playback with MP3/WMA/AAC/WAV/FLAC/APE compatibility
- USB Firmware Upgrade

Inputs:

- 2 x SPDIF (Coax), 2 x SPDIF (Optical), 1 x PC USB (USB B),
- 1 x USB HDD (USB A), 1 x Bluetooth (aptX / aptX HD), 1 x AES3/EBU

Outputs: 1 x RCA, 1 x XLR, 1 x Headphone, 2 x 12V Trigger, 1 x Optical, 1 x COAX outputs

Sampling Frequency:

- Optical/Coaxial: 44.1kHz → 192kHz
- USB HDD: 44.1kHz → 96kHz
- PC USB: 44.1kHz → 768kHz (PCM) / DSD64, DSD128, DSD256, DSD512

DAC

D to A Converter: ES9038Pro

Output Level (0dBFS, 1kHz): 2.05Vrms (RCA), 4.1Vrms (XLR)

Total Harmonic Distortion (THD): < 0.001% (1kHz @ 0dBFS)

Frequency Response: 20Hz-20kHz (+/-0.1dB)

Output Impedance: Not specified

Max. Sampling Frequency:

- USB HDD: 96kHz
- Optical, Coaxial: 192kHz
- PC USB: PCM768kHz, DSD512

Signal-to-Noise Ratio (S/N)

- > 118dB (A-weighted, RCA)
- > 123dB (A-weighted, XLR)

Headphone Amplifier

Total Harmonic Distortion(THD): < 0.01% (1kHz, 50mW)

Output Impedance: 2.35 ohm

Load Impedance: 20-600 ohm

General**Standby Power Consumption:** <0.5W**Net Weight:** 4.2 kg**Gross Weight:** 5.8 kg**Dimensions (mm) (W x H x D):** W: 315 x H: 88.3 x D: 277mm**Carton Size (mm) (W x H x D):** W: 409 x H: 220 x D: 451mm**Finish****Power Requirements (depending on region):**

- 220-240V ~ 50/60Hz
- 100-120V ~ 50/60Hz

Standard Accessories: Power Cord, Remote Control, User Manual, etc.