Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

BRITEQ BT-THEATRE 60FCL

Šifra: 20043
Kategorija prozivoda: TV i Pozorišna Rasveta
Proizvođač: BRITEQ



Cena: 46.800,00 rsd

General : Dimensions (cm)	24.1 x 25.1 x 19.5
General : Weight (kg)	3.63
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	62
General : Color	black
General : Display	LCD
General : Fixation	M10
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	4
Control : maximum DMX channels	7

Light : lamp socket	No
Light : Lux	389lx (beam 17°, 5m)
Light : lamp	COB
Light : min. color temperature (K)	2700
Light : max. color temperature (K)	5600
Light : colors	Red, Green, Blue, Lime, RGBL
Light : mix colors	Yes
Light : functions	manual zoom
Light : zoomrange	N/A
Light : min. beam angle (°)	17
Light : max. beam angle (°)	40
Light : max. refresh rate (kHz)	3.6
Connections : input	3 pin XLR, rdm, Schuko CEE 7/7
Connections : output	3 pin XLR

Stylish full color LED theater spot with manual 17° - 40° zoom
Thanks to its attractive looks this projector is perfect for use in clubs, exhibition booths, rental, ...
Four-leaf barndoor included
No more heavy and expensive dimmer packs needed!
Thanks to the 60W RGBL LED, you can create rich colors and excellent white tints with a high CRI >87
Different color presets, including white with different CCT: 2700K, 3000K, 3200K, 4000K, 5600K
Low noise, temperature controlled, cooling fan
Extruded black anodized aluminium housing with strong bracket
LCD-display to select different working modes:
Standalone (master) Mode : set dimmer + strobe (if needed)
Master/slave mode: connect several projectors together, the first projector controls the others
DMX-controlled: 6 different channel modes for maximum flexibility
Selectable lamp behavior: halogen lamp (slow) or led (fast)
Four dimmer curves: linear, square, inverse square, S-curve
In case of DMX failure you can choose between blackout and freeze mode
RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
Lock function to avoid unwanted altering of the settings
White balance adjustment to perfectly match the colors of several projectors
Default factory settings + user settings can be saved/loaded
3pin DMX in/outputs and fixed 1m power cord with standard mains plug (CEE 7/7)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.