

Reloop RP-7 - Gramofon

Šifra: 20097

Kategorija proizvoda: DJ Gramofoni

Proizvođač: Reloop



Cena: 65.880,00 rsd

Features

Industry-first, series-manufactured, professional 7" direct-drive DJ turntable system
Quartz-controlled 7" turntable with high-torque direct-drive motor
Exclusively developed for the 45s DJ and vinyl enthusiast scene
Newly developed brushless DC motor with 2.5 kg/cm torque
Powerful torque for reliable vinyl cueing and advanced scratching techniques
Solid construction with a refined chassis and superior tonearm design
Precision-machined, die-cast aluminium platter
Finely tuned motor characteristics to minimise wow and flutter
Height-adjustable VTA tonearm base from the best-selling RP-7000/8000 series
Straight copper tonearm with internal rubber damping for superior vinyl tracking and minimal resonance
Statically-balanced, straight tonearm system with hydraulic lift, eliminating the need for anti-skating
Universal cartridge system connection (SME, headshell cartridges recommended)
Precise motor control with three speeds (33 1/3, 45 and 78 RPM)
Clickless tempo fader and adjustable tempo range supporting +/-8 %, +/-16 % or +/-35 %
Pitch reset toggle button and clearly indicated tempo scale
Recessed connection terminal for a flush setup
Gold-plated phono and line output
Newly developed internal switching power supply to reduce unwanted interference
Aluminium vinyl puck adapter with recessed storage slot
Strobe light indicator for all turntable speed settings
IEC connection with detachable mains and RCA cables
Detachable and freely rotatable LED needle illuminator in unibody aluminium design
Robust construction and high-quality finish in deep black metallic
Incl. turntable platter, vinyl puck, slipmat, slip sheet, LED needle light, counterweight, phono RCA cable with grounding, mains cable and instruction manual, (headshell and cartridge sold separately)

Technical Data

Turntable:
Type: 3-speed fully manual
Drive: Direct drive
Motor: 8-pole, 3-phase, high-torque brushless DC motor
Speeds: 33 1/3, 45, 78 RPM
Pitch: ±8, 16, 35%
Starting Torque: 2.5 kgf/cm (starting at 78 rpm)
Start-Up Time: < 1 sec.
Brake System: Electronic brake

Platter:

215 mm dia. die-cast aluminium

Tonarm:

Type: Static balanced straight-shaped tonearm

Overhang: 0 mm

Offset Angle: 9,5°

VTA setting range: 0 - 6 mm

Effective Tonearm Length: 164.5 mm

Wow and Flutter: Less than 0.15% WTD at 3 KHz RMS

S/N Ratio: More than 75 dB (A-w./20 KHz LPF)

Applicable Cartridge Weight: 15 ~ 20 g (including headshell)

Connections:

1x Phono/Line Out (gold-plated), 1x GND earth connection

General:

Power Input: AC 100-240 V, 50/60 Hz

Power Consumption: 3 W

Dimensions: 350(W) x 270(D) x 139(H) mm

Weight: 5.7 kg

Incl. turntable platter, vinyl puck, slipmat, slip sheet, LED needle light, counterweight, phono RCA cable with grounding, mains cable and instruction manual, (headshell and cartridge sold separately)