

Technics SL-G700M2-S - Plejer

Šifra: 20140

Kategorija proizvoda: Network Plejeri

Proizvođač: Technics



Cena: 359.880,00 rsd

Covers Most of the Digital Audio Media Available Today:

- Super Audio CD (Single/Hybrid 2ch) / CD Playback
- Network Supports to High-res Digital Audio Files Including MQA
- MQA-CD Playback
- Google Cast™ / Works with Google Assistant
- Spotify Connect
- Amazon Music
- Deezer
- TIDAL
- Qobuz
- Internet Radio
- AirPlay 2
- Bluetooth®

Grand Class High-quality Sound

- High Precision Coherent D/A Converter (Coherent Processing, High-performance D/A Converter ESS ES9026PRO in Dual Monaural Configuration, A Proprietary Discrete Amplifier Circuit)
- Multi-Stage Silent Power Supply (High-speed Switching Power Supply, Low-noise Regulator, Current Injection Active Noise Cancelling)
- Pure Disc Playback Mode for Super Audio CD/CD Playback for Greater Sound Purity
- Supports Higher Grade Headphone Connection with Class AA Headphone AMP

High-quality Technics Design

- Four-Section Configuration
- High-Rigidity Chassis and Aluminium Die-cast Disc Tray - High-Stability SACD Mechanism
- 7mm Thick Aluminium Plate Used for the Front Panel
- Control Port for System Control with SU-G700

Disc Compatibility

- Super Audio CD (2 ch area only), CD, CD-R, CD-RW

Disc Format

- Super Audio CD, CD-DA

Frequency Response

- Super Audio CD: 2 Hz to 50 kHz (-3 dB) / CD: 2Hz to 20 kHz (-3 dB)

Dynamic Range (IHF-A)

- Super Audio CD: BALANCED: 110dB (IHF-A) / UNBALANCED: 110dB (IHF-A)
- CD: BALANCED: 98dB (IHF-A) / UNBALANCED: 98dB (IHF-A)

Signal to Noise Ratio (IHF-A)

- Super Audio CD: BALANCED: 121 dB / UNBALANCED: 118 dB
- CD: BALANCED: 121 dB / UNBALANCED: 118 dB

THD+N

- Super Audio CD: 0.0006% (1 kHz, 0 dB) / CD: 0.0015% (1 kHz, 0 dB)

Digital Input Terminal

- Coaxial Digital x 1, Optical Digital x 1, USB-A x 2(Front/Rear), USB-B x1

Analogue Output Terminal

- BALANCED x 1, UNBALANCED x 1
- Support Variable Level Output

Digital output Terminal

- Coaxial Digital x 1, Optical Digital x 1

System Port

- System Control (Φ3.5 mm Jack)

Headphone Output

- Φ6.3 mm, 110 mV, 32 Ω VOL MAX

USB-A**Support Codec**

WAV: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit

FLAC: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit

DSD: 2.8, 5.6, 11.2 MHz

AIFF: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit

ALAC: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit

AAC: 32, 44.1, 48, 88.2, 96 kHz / 16-320 kbps

MP3: 32, 44.1, 48 kHz / 16-320 kbps

USB-B Support Codec

- PCM: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit

- DSD: 2.8, 5.6, 11.2 MHz

Network Playback Support Codec

WAV: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit

FLAC: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit

DSD: 2.8, 5.6, 11.2 MHz

AIFF: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24, 32 bit

ALAC: 32, 44.1, 48, 88.2, 96, 176.4, 192, 352.8, 384 kHz / 16, 24 bit

AAC: 32, 44.1, 48, 88.2, 96 kHz / 16-320 kbps

MP3: Yes (32, 44.1, 48 kHz / 16-320 kbps)

Ethernet Interface

- LAN (100 Base-TX / 10 Base-T)

Wi-Fi

- IEEE 802.11 a/b/g/n/ac, 2.4 GHz / 5 GHz Band

Bluetooth(Support codec)

- AAC, SBC

Power Supply

- AC 220-240 V, 50 Hz / 60 Hz

Power Consumption/ Standby

- 45W/ 2W(Network Standby On)

Dimensions (W x H x D)

- 430 x 98 x 407 mm

Weight

- Approx. 12.3 kg

Accessories

- Remote Control, AC Cord, System Connection Cable, Analogue Audio cable,
- Owner's Manual

Note

** Network content services are operated by their respective service providers, and service may be discontinued either temporarily or permanently without notice. Some content may not be available in the country in which you reside.*