

BRITEQ BT-THEATRE HD2

Šifra: 20368
Kategorija proizvoda: TV i Pozorišna Rasveta
Proizvođač: BRITEQ

Cena: 128.280,00 rsd



A powerful "ALL-IN-1" LED theater spot with motorized 14° ~ 55° zoom.
No more need for separate white and color projectors, BT-THEATRE HD2 does it all:
Perfect WHITE with high CRI > 90Ra and CCT presets
Rich COLOR selection with color presets!
Thanks to the new CCS Color Calibration System the color differences between different batches is a problem of the past!
Different CCT presets for white: ..., 2700K, ..., 3000K, 3200K, ..., 4000K, ..., 5600K, ...
Different color presets (LEE® / ROSCO® numbering)
Based on a 200watt 5-color RGBAL-LED (Red, Green, Blue, Amber, Lime)
Very silent operation: heat-pipe technology with low noise cooling fan and different presets (live, studio, ...)
DMX-controlled: 4 different channel modes for maximum flexibility
RDM-functionality for easy remote setup: DMX addressing, channel mode, ...
Flicker free TV-recordings thanks to the adjustable high LED-refresh rate!
Four dimmer settings with different behavior & speed.
Manual control for dimming, colors, CCT & zoom.
OLED-display to navigate easily through the setup menu!
In case of DMX failure, you can choose between blackout and freeze mode.
Lock function to avoid unwanted altering of the settings.
Rugged extruded aluminum housing.
3 & 5pin DMX in/outputs + PowerCON in/outputs for easy daisy chaining.
An 8-leaf barndoor (BT-THEATRE BARN2) is optionally available.

General : Dimensions (cm)	45 x 29 x 26
General : Weight (kg)	7.56
General : Powerinput	AC 100 - 240V, 50/60Hz
General : Energy Label	No
General : Power consumption W	240
General : Color	black

General : Display	OLED
General : Fixation	optional standard clamp
General : IP rating	indoor
Control : Modes	standalone fixed, manual, DMX
Control : Protocol	DMX, RDM
Control : programmable	No
Control : upgradable software	Yes
Control : minimum DMX channels	3
Control : maximum DMX channels	19
Light : lamp socket	No
Light : Lux	1428 (@5m beam 14°)
Light : lamp	LED
Light : min. color temperature (K)	1800
Light : max. color temperature (K)	8000
Light : CRI	90
Light : colors	Red, Green, Blue, Amber, Lime, RGBAL
Light : mix colors	No
Light : functions	motorized zoom
Light : min. beam angle (°)	14
Light : max. beam angle (°)	55
Light : max. refresh rate (kHz)	25
Connections : input	3 pin XLR, 5 pin XLR, rdm, PowerCon® or compatible
Connections : output	3 pin XLR, 5 pin XLR, PowerCon® or compatible