

Zoom H5studio - Snimač

Šifra: 20426

Kategorija proizvoda: Snimači/Rekorderi

Proizvođač: ZOOM

Cena: 47.880,00 rsd



Features

- Large-diameter XY stereo microphone capsule (19.4 mm)
- Dual AD converter + 32-bit float support for clip-free recording
- 16/24-bit depth available
- 4 track simultaneous recording at up to 192kHz sampling in WAV format
- 2 XLR/TRS phone inputs (48V, +4dBu input compatible)
- F-series preamps
- Color LCD screen
- Compatible with Zoom capsule system 3.0
- 4-in/2-out USB audio interface
- 9 hours of battery life on AA battery (2x) or USB-C power

INPUT AND OUTPUT CHANNELS

Inputs

- Mic capsule: 1
- MIC/LINE (mono): 2

Outputs

- LINE OUT: 1
- Headphone: 1
- Built-in speaker (mono): 1

INPUTS

XY mic: XYH-5s

90° XY stereo format

Pickup pattern: Unidirectional

Sensitivity: -41 dB/Pa at 1 kHz

Maximum sound pressure input: 140 dB SPL

MIC/LINE IN: XYH-5s

Connector: 1 stereo mini jack

Input gain: $-\infty$ - +60 dB

Input impedance: 2 k Ω or more

Plug-in power: 2.5 V

MIC/LINE (mono)

Connectors:

- 2 XLR/TRS combo jacks
- (XLR \square 2 HOT TRS \square TIP HOT \square)

Input gain: $-\infty$ - +60 dB

Input impedance MIC:

- 3 k Ω or more

- LINE: 3 k Ω or more

Maximum input level:

- MIC: +4 dBu
- LINE: +24 dBu

Phantom power: +48 V

Equivalent input noise: -127 dBu or less (IHF-A) at 150 Ω input

OUTPUTS**LINE OUT**

Connector: 1 stereo mini jack

Maximum output level: +1 dBu

Output impedance: 110 Ω or less

Headphone

Connector: 1 stereo mini jack

Maximum output level: 20 mW + 20 mW when 32 Ω load

Output impedance: 10 Ω or less

Built-in speaker

Type: 20 mm x 30 mm elliptical dynamic speaker

Effective maximum output: 250 mW

RECORDER

Maximum simultaneous recording tracks: 6

Maximum simultaneous playback tracks: 4

Recording formats:

- WAV
- 44.1/48/96/192 kHz,
- 16-bit/24-bit/32-bit float
- mono/stereo
- BWF and iXML formats supported

Recording media:

- microSDHC memory cards
- microSDXC memory cards

DISPLAY

2.00" full-color LCD: 320 x 240

USB**Connector:**

- USB Type-C
- Use a USB cable that supports data transfer.

Audio Interface:

- USB 2.0 High Speed
- Input and output channels: 4 in / 2 out (Multi)
- 2 in / 2 out (Stereo)
- Sampling frequencies:

44.1/48/96 kHz (audio interface only)

44.1/48 kHz (audio interface + onboard recording)

- Bit depths: 24-bit, 32-bit float

File transfer: USB 2.0 High Speed

REMOTE

Dedicated wireless adapter: ZOOM BTA-1

POWER

4 AA batteries: Alkaline, lithium or rechargeable NiMH batteries

AC Adapter:

- ZOOM AD-17 (DC 5 V/1 A)
- USB bus power is supported.

ESTIMATED CONTINUOUS OPERATION TIMES USING BATTERIES : 2-track (XYH-5s) recording

Alkaline batteries: About 15 hours

NiMH batteries (1900 mAh): About 13 hours

Lithium batteries: About 21 hours

ESTIMATED CONTINUOUS OPERATION TIMES USING BATTERIES : 4-track (XYH-5s and inputs 1-2) recording

Alkaline batteries: About 6 hours

NiMH batteries (1900 mAh): About 6 hours

Lithium batteries: About 11.5 hours

Power consumption: 5 W maximum

Dimensions: 86.0 mm (W) × 206.0 mm (D) × 54.6 mm (H)

Weight: 410 g (including batteries)