

Biamp Commercial Audio PM4100

Šifra: 20437

Kategorija proizvoda: PA Predpojačala

Proizvođač: Biamp



Cena: 59.880,00 rsd

GENERAL

Height: 1.5 inches (37 mm)

Width: 8.6 inches (218 mm)

Depth: 2.8 inches (70 mm)

Weight: 1.1 lbs (0.5 kg)

ENVIRONMENTAL

Ambient Operating Temperature Range: 32 - 86° F (0 - 30° C)

Humidity: 10-90% relative humidity (non-condensing)

Altitude: 0-6,600 ft (0-2000m) MSL

POWER

Power: Main: 12V DC 5W

PoE Input: PoE: IEEE 802.3at Class 2, 7W

Cooling: Convection

NETWORK

Network Connection(s): RJ-45 with Ethernet (CAT5e or better)

Number of Ports: 1 LAN Port

CONTROLS & INDICATORS

Logic I/O:

- GPIO
- Number of Ports: 4
- Connector: 5-pin, 0.3-inch Euroblock
- Type: Open drain
- Input Trigger Low: < 1V DC
- Input Trigger High: > 4V DC
- Isolated Output: No
- Max Voltage: 24V DC
- Max Current: 0.5 A

RS-232:

- RS-232 / IR
- Number of Ports: 2 (bidirectional)
- Connector: 3-pin, 0.3-inch Euroblock
- Baud Rate: 1200 - 115200 bit/sec
- Data Bits: 7, 8
- Parity: Even, Odd, None
- Stop Bits: 1, 2

- IR Frequency Range: 400 Hz to 500 kHz

AUDIO

Inputs:

- Number of Inputs: 4 (stereo)
- Connector: RCA
- Input Impedance: < 100k Ω
- Max Input Level: 2 Vrms
- Input Gain (adjustable): \pm 12 dB
- Wake on Signal: Adjustable level

Outputs:

- Number of Outputs: 1 (stereo)
- Output impedance: 100 Ω
- Output Level (@ 0 dB FS): 1.3 Vrms
- Connector: 5-pin, 0.3-inch Euroblock

USB: Connector: USB 2.0 Type-B Bit Depth: 16-bit Sample Rate: 48kHz

COMPLIANCE

Certifications:

- FCC Part 15B (USA)
- UL listed (USA and Canada)
- CE Marked (Europe)
- RoHS Directive (Europe)