Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

BIAMP Desono DX-S5-B Black



Šifra: 20443
Kategorija prozivoda: Nazidni Zvučnici
Proizvođač: Biamp

Cena: 28.680,00 rsd

GENERAL
Height: 11.03 inches (280 mm)
Width: 7.09 inches (180 mm)
Depth: 7.28 inches (185 mm)
Weight: 10.3 lbs (4.7 kg)
Finish: RAL Color: Black RAL 9017
Enclosure:
• High impact ABS plastic
• Bracket: Heavily reinforced glass-filled nylon with UV-resistant painted, matte finish cover
Mounting: ClickMount pan-tilt bracket
Included Accessories: ClickMount pan-tilt bracket
Optional Accessories:
• SPA-UBDX100 [-B/-W] U-Bracket with ClickPlug
• CMX-SM [-B/-W] ClickMount pan-tilt bracket
Required Accessories: 75 Hz, 12 dB/ oct. high pass filter
Recommended Amplifiers: Passive: 100 W - 200 W into 8 Ω, (28 V - 40 V)

ENVIRONMENTAL
Operating Environment: Indoor / Outdoor Direct Exposure

POWER
Power:
• 100W Cont.
• 400W Peak
Power Consumption:
• Rated Continuous Voltage:
• Passive 15.3 V (24 dBV)

CONTROLS & INDICATORS
Control: Wattage / low impedance selector switch

LOUDSPEAKER
Loudspeaker Type: 2-way, 5-inch, high output, coaxial, surface mount loudspeaker
Operating Mode: Single Amplified with DSP
Operating Range: (-10 dB): 75 Hz - 20 kHz
Beamwidth: (Nominal Beamwidth (H x V) 130° x 125°
Transducers:
• LF 1 x 5 inch (127 mm)
• HF 1 x 1 inch (25 mm) exit compression driver

Autoformer:
• 70V: 60W, 30W, 15W, 7.5W
• 100V: 60W, 30W, 15W
Sensitivity:
• 92 dB (2.83 V)
• 91 dB (1 W at rated impedance)
Dispersion: (H x V) 130° x 125°
Drivers:
• LF 1 x 5 inch
• HF 1 x 1 inch

AUDIO
Input Type: Lever-actuated wire clamping 4-position terminal block with pass-through
Impedance: 6Ω
Maximum Output:
• Max Output @1m: 109 dB
• 117 dB Peak
SPL:
• Nominal Maximum SPL: Passive:
Peak = 115 dB | Continuous = 109 dB
• Rated Maximum SPL (Processed): Passive:
Peak = 117 dB | Continuous = 105 dB

CERTIFIED SOLUTIONS
Zoom: Zoom Certified

COMPLIANCE
Certifications:
• ETL listed to comply with UL 1480A
• CSA STD C22.2# 62368-1
Environmental Ratings:
• IP54 per IEC 60529
• IEC 60068-2-5 (Solar Radiation)
• IEC 60068-2-11 (Salt Mist)
• IEC 60068-2-42 (SO2)
• IEC 60068-2-60 (Chlorine)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.