

## BIAMP Desono DX-S5-B Black

Šifra: 20443

Kategorija proizvoda: Nazidni Zvučnici

Proizvođač: Biamp



**Cena: 28.680,00 rsd**

### GENERAL

**Height:** 11.03 inches (280 mm)

**Width:** 7.09 inches (180 mm)

**Depth:** 7.28 inches (185 mm)

**Weight:** 10.3 lbs (4.7 kg)

**Finish: RAL Color:** Black RAL 9017

**Enclosure:**

- High impact ABS plastic
- Bracket: Heavily reinforced glass-filled nylon with UV-resistant painted, matte finish cover

**Mounting:** ClickMount pan-tilt bracket

**Included Accessories:** ClickMount pan-tilt bracket

**Optional Accessories:**

- SPA-UBDX100 [-B/-W] U-Bracket with ClickPlug
- CMX-SM [-B/-W] ClickMount pan-tilt bracket

**Required Accessories:** 75 Hz, 12 dB/ oct. high pass filter

**Recommended Amplifiers:** Passive: 100 W - 200 W into 8  $\Omega$ , (28 V - 40 V)

### ENVIRONMENTAL

**Operating Environment:** Indoor / Outdoor Direct Exposure

### POWER

**Power:**

- 100W Cont.
- 400W Peak

**Power Consumption:**

- Rated Continuous Voltage:
- Passive 15.3 V (24 dBV)

### CONTROLS & INDICATORS

**Control:** Wattage / low impedance selector switch

### LOUDSPEAKER

**Loudspeaker Type:** 2-way, 5-inch, high output, coaxial, surface mount loudspeaker

**Operating Mode:** Single Amplified with DSP

**Operating Range:** (-10 dB): 75 Hz - 20 kHz

**Beamwidth:** (Nominal Beamwidth (H x V) 130° x 125°

**Transducers:**

- LF 1 x 5 inch (127 mm)
- HF 1 x 1 inch (25 mm) exit compression driver

**Autoformer:**

- 70V: 60W, 30W, 15W, 7.5W
- 100V: 60W, 30W, 15W

**Sensitivity:**

- 92 dB (2.83 V)
- 91 dB (1 W at rated impedance)

**Dispersion:** (H x V) 130° x 125°

**Drivers:**

- LF 1 x 5 inch
- HF 1 x 1 inch

**AUDIO**

**Input Type:** Lever-actuated wire clamping 4-position terminal block with pass-through

**Impedance:** 6Ω

**Maximum Output:**

- Max Output @1m: 109 dB
- 117 dB Peak

**SPL:**

- Nominal Maximum SPL: Passive:  
Peak = 115 dB | Continuous = 109 dB
- Rated Maximum SPL (Processed): Passive:  
Peak = 117 dB | Continuous = 105 dB

**CERTIFIED SOLUTIONS**

**Zoom:** Zoom Certified

**COMPLIANCE****Certifications:**

- ETL listed to comply with UL 1480A
- CSA STD C22.2# 62368-1

**Environmental Ratings:**

- IP54 per IEC 60529
- IEC 60068-2-5 (Solar Radiation)
- IEC 60068-2-11 (Salt Mist)
- IEC 60068-2-42 (SO<sub>2</sub>)
- IEC 60068-2-60 (Chlorine)