Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

SEQUENTIAL Prophet-6 - Modul



Šifra: 20480
Kategorija prozivoda: Sound Moduli
Proizvođač: Sequential

Cena: 287.880,00 rsd

Oscillators:
• 2x discrete VCOs per voice
• Wave Shape per Oscillator (Continuously Variable): Triangle, sawtooth, pulse, and square
• Pulse width per oscillator
• Hard Sync: Oscillator 1 syncs to oscillator 2
• Triangle Sub-Octave Generator: Oscillator 1 per voice
• Low-Frequency Mode: Oscillator 2
• Keyboard Tracking: On/off (oscillator 2)
• Oscillator Slop: For increased tuning instability, from subtle to extreme

Mixer:
• Oscillator 1 amount
• Oscillator 1 sub-octave amount
• Oscillator 2 amount
• White noise amount

High Pass Filter:
• 2-pole, resonant, high-pass filter per voice
• Bi-polar filter envelope amount
• Velocity modulation of envelope amount
• Keyboard Tracking: Off, half, full

Low Pass Filter:
• 4-pole, resonant, low-pass filter per voice
• Filter can be driven into self-oscillation with the Resonance control
• Bi-polar filter envelope amount
• Velocity modulation of envelope amount
• Keyboard tracking: Off, half, full

Envelope Generators:
• Filter Envelope: Four-stage (ADSR) envelope generator
• Amplifier Envelope: Four-stage (ADSR) envelope generator with velocity modulation of envelope amount

LFO:
• 5x Wave Shapes: Triangle, sawtooth, reverse sawtooth, square, and random (sample and hold)
• Clock sync (internal or external MIDI clock)
• Initial amount
• Mod Destinations: Oscillator 1 frequency, oscillator 2 frequency, oscillator 1 and 2 pulse width, low-

pass filter cutoff, high-pass filter cutoff

Poly Mod:
• Sources: Filter envelope (bi-polar) and oscillator 2 (bi-polar)
• Destinations: Oscillator 1 frequency, oscillator 1 shape, oscillator 1 pulse width, low-pass filter cutoff, high-pass filter cutoff

Aftertouch:
• Source: Channel (mono) aftertouch with bi-polar amount
• Destinations: Oscillator 1 frequency, oscillator 2 frequency, LFO amount, amplifier envelope amount, low-pass filter envelope amount, high-pass filter envelope amount

Clock:
• Master clock with tap tempo
• BPM control and display
• MIDI clock sync

Arpeggiator:
• Selectable Note Value: 16th note, 8th note triplet, 8th note, dotted 8th note, quarter note
• 1, 2, or 3 octave range
• Up, down, up/down, random, and assign modes

Sequencer:
• Polyphonic Step Sequencer: 64 steps and rests

Effects:
• Stereo analog distortion
• Dual, 24-bit, 48 kHz Digital Effects: Reverb (room, hall, plate, spring), delay (full bandwidth digital delay and emulated bucket brigade and tape delays), chorus, and phase shifter
• Delay sync
• True Bypass: Maintains fully analog signal path when digital effects are off

Controls:
• Polyphonic Glide: Portamento
• Hold Switch: Latches held notes on Unison (Monophonic) Mode: Configurable voice count, from one to all six voices, and key modes
• Preset Switch: When off, the front panel is live; what you see is what you hear

Patch Memory:
• 1000 Programs: 500 user / 500 factory programs in 10 banks of 100 programs each
• Direct Program Access: Prophet 5-style single-button access to the current set of 10 programs

Input & Output:
• Left/Mono & Right Audio Outputs: 2 x 1/4" / 6.35 mm phone jack
• Headphone Output: Stereo, 1/4" / 6.35 mm phone jack
• MIDI: In, out, and thru ports
• USB: Bi-directional MIDI communication
• Low-pass filter cutoff expression pedal input
• Volume expression pedal input
• Sustain footswitch input
• Sequencer start/stop footswitch input

Power:
• 100/240 volts at 50/60 Hz
• Power Consumption: 30 W maximum
• IEC AC power inlet for internal power supply

Dimensions:
• 21.3 x 7.4 x 4.4" / 54.0 x 18.9 x 11.2 cm

Weight:
• 13.0 lb / 5.9 kg

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.