

## SEQUENTIAL Prophet-6 - Modul

Šifra: 20480

Kategorija prozivoda: Sound Moduli

Proizvođač: Sequential

**Cena: 287.880,00 rsd**

- Keyboard Tracking: On/off (oscillator 2)

- Oscillator Slop: For increased tuning instability, from subtle to extreme

### **Mixer:**

- Oscillator 1 amount
- Oscillator 1 sub-octave amount
- Oscillator 2 amount
- White noise amount

### **High Pass Filter:**

- 2-pole, resonant, high-pass filter per voice
- Bi-polar filter envelope amount
- Velocity modulation of envelope amount
- Keyboard Tracking: Off, half, full

### **Low Pass Filter:**

- 4-pole, resonant, low-pass filter per voice
- Filter can be driven into self-oscillation with the Resonance control
- Bi-polar filter envelope amount
- Velocity modulation of envelope amount
- Keyboard tracking: Off, half, full

### **Envelope Generators:**

- Filter Envelope: Four-stage (ADSR) envelope generator
- Amplifier Envelope: Four-stage (ADSR) envelope generator with velocity modulation of envelope amount

### **LFO:**

- 5x Wave Shapes: Triangle, sawtooth, reverse sawtooth, square, and random (sample and hold)
- Clock sync (internal or external MIDI clock)
- Initial amount
- Mod Destinations: Oscillator 1 frequency, oscillator 2 frequency, oscillator 1 and 2 pulse width, low-pass filter cutoff, high-pass filter cutoff

### **Poly Mod:**

- Sources: Filter envelope (bi-polar) and oscillator 2 (bi-polar)
- Destinations: Oscillator 1 frequency, oscillator 1 shape, oscillator 1 pulse width, low-pass filter cutoff, high-pass filter cutoff

### **Aftertouch:**

- Source: Channel (mono) aftertouch with bi-polar amount
- Destinations: Oscillator 1 frequency, oscillator 2 frequency, LFO amount, amplifier envelope amount, low-pass filter envelope amount, high-pass filter envelope amount

## SEQUENTIAL Prophet-6 Modul

## Clock:

- Master clock with tap tempo
- BPM control and display
- MIDI clock sync

## Arpeggiator:

- Selectable Note Value: 16th note, 8th note triplet, 8th note, dotted 8th note, quarter note
- 1, 2, or 3 octave range
- Up, down, up/down, random, and assign modes

## Sequencer:

- Polyphonic Step Sequencer: 64 steps and rests

## Effects:

- Stereo analog distortion
- Dual, 24-bit, 48 kHz Digital Effects: Reverb (room, hall, plate, spring), delay (full bandwidth digital delay and emulated bucket brigade and tape delays), chorus, and phase shifter
- Delay sync
- True Bypass: Maintains fully analog signal path when digital effects are off

## Controls:

- Polyphonic Glide: Portamento
- Hold Switch: Latches held notes on Unison (Monophonic) Mode: Configurable voice count, from one to all six voices, and key modes
- Preset Switch: When off, the front panel is live; what you see is what you hear

## Patch Memory:

- 1000 Programs: 500 user / 500 factory programs in 10 banks of 100 programs each
- Direct Program Access: Prophet 5-style single-button access to the current set of 10 programs

## Input & Output:

- Left/Mono & Right Audio Outputs: 2 x 1/4" / 6.35 mm phone jack
- Headphone Output: Stereo, 1/4" / 6.35 mm phone jack
- MIDI: In, out, and thru ports
- USB: Bi-directional MIDI communication
- Low-pass filter cutoff expression pedal input
- Volume expression pedal input
- Sustain footswitch input
- Sequencer start/stop footswitch input

## Power:

- 100/240 volts at 50/60 Hz
- Power Consumption: 30 W maximum
- IEC AC power inlet for internal power supply

## Dimensions:

- 21.3 x 7.4 x 4.4" / 54.0 x 18.9 x 11.2 cm

## Weight:

- 13.0 lb / 5.9 kg