logoe not found or type unknown

Firma: Player Plus doo Adresa: Svetogorska 9 Telefon: +381 11 3347 442 Fax: +381 11 3347 615

PIB: 106966344

E-mail: porudzbine@player.rs

DENON: PMA 520AE Black

DENON PMA 520AE Black

Šifra: 1343

Kategorija prozivoda: Integrisana Pojačala

Proizvođač: DENON

Cena: 27.480,00 rsd

The PMA-520AE integrated amplifier features a High-Current Single-Push-Pull circuitry to achieve both strength and detail in music playback, which is Denon's focus for its pure audio amplifiers. The relay switch used for CD and Phono input contains an inert gas to prevent the occurrence of noise that can negatively affect the signal. In addition, durable parts strictly selected for their contribution to sound quality, such as the large-capacity block capacitor for the power supply circuit, high-quality sound carbon resistors, and high-quality sound capacitors, are also used. Each individual part employed in configuring the circuits reflects this emphasis on high fidelity. For improved convenience, the remote control unit that comes with the PMA-520AE includes the main functions that control Denon CD players.

New features:

Improved sound quality	Newly-designed system remote control	ECO f
	New higher quality speaker terminals	and a

State-of-the-art Denon solutions for maximizing content quality

70 W x 2 ch (4 ohms)	High Current (HC) Single-Push-Pull Circuit	Wide
	Main transformer with separate power supplies	₩14f6

Vibration-resistant design with Direct Mechanical

Europ

Alum

Front

Ground Construction

Phono Equalizer Amp (MM)

Ease-of-use

ECO friendly with low power consumption in stand by and auto power off Remote also controls Denon CD players and network players

Color variations

Premium silver Black

Features

Channels 2

UHC-MOS single push pull circuit Image not found or type unknown

Advanced HC-TR single push pull circuit onage not found or type unknown

LC mounted twin transformer $\underline{\mathsf{Image}}\ \mathsf{not}\ \mathsf{found}\ \mathsf{or}\ \mathsf{type}\ \mathsf{unknown}$

Wide range amplifier page not found or type unknown

High current dynamic power supply $\varrho_{\text{nage not found or type unknown}}$

Power amp discrete construction on to possession of the power amp discrete construction on the power amp discrete construction of the p

Micro processor auto off page not found or type unknown

Solid Heat Sinks
Image not found or type unknown O
Source Direct Image not found or type unknown —
Power Amp direct Image not found or type unknown O O O O
Balance / Bass / Treble / Loudness / / / / Image not fourlish ag éypæt diouk nich ag é
Dac Mode
Digital in: USB-A / USB-B / optical / coaxial Image not found or type unknown
Sample Rate digital In Image not found or type unknown
Asynchronous mode rear USB Image not found or type unknown
Bit-perfect transmission Image not found or type unknown
USB-B DSD Audio Streaming (DoP): DSD2.8 / DSD5.6 Image not found or type unknown
Ground isolator for DAC Mode operation Image not found or type unknown
AL 32 Processing Image not found or type unknown —
DAC Master Clock Design Image not found or type unknown -
Bluetooth / aptX / NFC Image not found or type unknown
Vertical Installation Image not found or type unknown —
Low Noise OELD display Image not found or type unknown Inputs/Outputs Audio Inputs 6

Dhana Innut. MM / MC

0

```
Image not fourlish age typet toknown type unknown
Audio Outputs 1
Pre-out / Main-in
                  Image not fourlish ageyppet stokend won type unknown
Power Amp Direct IN
                      Image not found or type unknown
Gold plated Cinch
                   Image not found or type unknown
Speaker A / B
               Image not found or type unknown
Number of terminals 1
                             0
Remote Control Bus in / out
                             Image not found or type unknown
Headphone Out
                 Image not found or type unknown
Specifications
Output power 8 Ohm (20 Hz - 20 kHz, T.H.D. 0.07%) 45 W
Output power 4 Ohm (1 kHz, T.H.D. 0.7%) 70 W
Total Harmonic Distortion 0.02 %
Input Sensitivity: MM 2.5 mV / 47 kohm
Input Sensitivity: MC
                      Image not found or type unknown
Signal to Noise Ratio: MM/MC 84 dB /
                                        Image not found or type unknown
Input Sensitivity: High level 110 mV / 30 kohms
Signal to Noise Ratio: High level 105dB
Treble Control ± 8 dB at 10 kHz
Bass Control ± 8 dB at 100 Hz
General
                                                       0
Available Colours: Premium Silver / Black
                                            Image not fourthageypet toknown type unknown
                   0
Metal Front Panel
                   Image not found or type unknown
Power Consumption in W 185
Standby Consumption in W 0.3
Auto Power Off
                Image not found or type unknown
Detachable Power Cable
```

0

Remote Control RC-1173

Λ

System Remote Function

Image not found or type unknown

Maximum Dimensions (W x D x H) in mm 434 x 308 x 121 Weight in kg 6.8