

DENON PMA 520AE Silver

Šifra: 1344

Kategorija proizvoda: Integrisana Pojačala

Proizvođač: DENON

Cena: **27.480,00** rsd.



The PMA-520AE integrated amplifier features a High-Current Single-Push-Pull circuitry to achieve both strength and detail in music playback, which is Denon's focus for its pure audio amplifiers. The relay switch used for CD and Phono input contains an inert gas to prevent the occurrence of noise that can negatively affect the signal. In addition, durable parts strictly selected for their contribution to sound quality, such as the large-capacity block capacitor for the power supply circuit, high-quality sound carbon resistors, and high-quality sound capacitors, are also used. Each individual part employed in configuring the circuits reflects this emphasis on high fidelity. For improved convenience, the remote control unit that comes with the PMA-520AE includes the main functions that control Denon CD players.

New features:

Improved sound quality

Newly-designed system remote control

ECO f
and a

New higher quality speaker terminals

State-of-the-art Denon solutions for maximizing content quality

70 W x 2 ch (4 ohms)

High Current (HC) Single-Push-Pull Circuit

Wide

Main transformer with separate power supplies

MAEF6

Vibration-resistant design with Direct Mechanical Ground Construction

Europ

Phono Equalizer Amp (MM)

Alumi

Ease-of-use

ECO friendly with low power consumption in stand by and auto power off

Remote also controls Denon CD players and network players

Front

Color variations

Premium silver

Black

Features

Channels 2

UHC-MOS single push pull circuit ✗

Advanced HC-TR single push pull circuit ✓

LC mounted twin transformer ✗

Wide range amplifier ✓

High current dynamic power supply ✓

Power amp discrete construction ✓

Micro processor auto off ✓
Solid Heat Sinks ✓
Source Direct ✓
Power Amp direct ✗
Balance / Bass / Treble / Loudness ✓ / ✓ / ✓ / ✓

Dac Mode

Digital in: USB-A / USB-B / optical / coaxial ✗
Sample Rate digital In ✗
Asynchronous mode rear USB ✗
Bit-perfect transmission ✗
USB-B DSD Audio Streaming (DoP): DSD2.8 / DSD5.6 ✗
Ground isolator for DAC Mode operation ✗
AL 32 Processing ✗
DAC Master Clock Design ✗
Bluetooth / aptX / NFC ✗
Vertical Installation ✗
Low Noise OELD display ✗

Inputs/Outputs

Audio Inputs 6
Digital in: USB-B / optical / coaxial ✗ / ✗ / ✗
Phono Input: MM / MC ✓ / ✗
Audio Outputs 1
Pre-out / Main-in ✗ / ✗
Power Amp Direct IN ✗
Gold plated Cinch ✗
Speaker A / B ✗
Number of terminals 1
Remote Control Bus in / out ✓
Headphone Out ✓

Specifications

Output power 8 Ohm (20 Hz - 20 kHz, T.H.D. 0.07%) 45 W
Output power 4 Ohm (1 kHz, T.H.D. 0.7%) 70 W
Total Harmonic Distortion 0.02 %
Input Sensitivity: MM 2.5 mV / 47 kohm
Input Sensitivity: MC ✗
Signal to Noise Ratio: MM/MC 84 dB / ✗
Input Sensitivity: High level 110 mV / 30 kohms
Signal to Noise Ratio: High level 105dB
Treble Control ± 8 dB at 10 kHz
Bass Control ± 8 dB at 100 Hz

General

Available Colours: Premium Silver / Black ✓ / ✓
Metal Front Panel ✓
Power Consumption in W 185
Standby Consumption in W 0.3
Auto Power Off ✓
Detachable Power Cable ✓
Remote Control RC-1173
System Remote Function ✓
Maximum Dimensions (W x D x H) in mm 434 x 308 x 121
Weight in kg 6.8