

Reloop RP-5000 MK4 - DJ gramofon

Šifra: 20872

Kategorija proizvoda: DJ Gramofoni

Proizvođač: Reloop

Cena: 55.080,00 rsd



Features

- Next evolution direct-drive turntable engineered for professional performance and durability
- Newly developed brushless DC motor with 2.5 kg/cm industry-standard torque
- Redesigned chassis with optimised damping and improved anti-vibration feet
- Quartz-controlled turntable with high-torque direct-drive motor
- Newly developed brushless DC motor with 2.5 kg/cm torque
- Powerful torque for reliable vinyl cueing and advanced scratching techniques
- Solid, damped construction with a refined chassis and proven tonearm design
- Precision-machined, die-cast aluminium platter
- Finely tuned motor characteristics to minimise wow and flutter
- Statically balanced S-shaped tonearm with hydraulic lift and anti-skating mechanism
- Universal cartridge system connection (SME)
- Precise motor control with three speeds (33 1/3, 45 and 78 RPM)
- Clickless tempo fader and adjustable pitch range supporting +/-8 %, +/-16 % or +/-50 %
- Pitch reset toggle button and clearly indicated tempo scale
- Reverse function: switch for forward/reverse playback
- Recessed connection terminal for a flush setup
- Gold-plated phono output
- Newly developed internal switching power supply to reduce unwanted interference
- Recessed puck storage slot and headshell stand
- Strobe light indicator for all turntable speed settings
- IEC connection with detachable mains and RCA cables
- Integrated pop-up stylus LED target light, button-activated
- Prepared for dust cover (available as optional accessory)
- New Shock-absorbing feet to further reduce unwanted vibrations
- Robust construction and high-quality finish in deep black metallic
- Incl.: Turntable platter, slipmat, slip sheet, counterweight, phono RCA cable with grounding, mains cable and instruction manual, (headshell and cartridge sold separately)

Technical Data

Turntable:

- Type: 3-speed fully manual
- Drive: Direct drive
- Motor: 8-pole, 3-phase, brushless DC motor
- Speeds: 33 1/3, 45, 78 RPM
- Pitch: ±8, 16, 50%
- Starting Torque: > 2.0 kgf/cm
- Start-Up Time: < 1 sec.

- Brake System: Electronic brake

Platter:

- 332 mm dia., Aluminum

Tonarm:

- Type: Static balanced S-shaped
- Overhang: 15 mm
- Tracking Error Angle: < 3°
- Tracking Force Adjustment Range: 0-4 g
- Applicable Cartridge Weight: 3.5-8.5 g
- Anti-Skating Range: 0-7 g
- Wow and Flutter: Typical: < 0.08% WTD at 3 kHz RMS, Limit: < than 0.12% WTD at 3 kHz RMS
- S/N Ratio: Typical: >60 dB, Limit: >55 dB

Connections:

- 1x Phono Out (gold-plated), 1x GND earth connection

General:

- Power Input: AC 100-240 V, 50/60 Hz
- Power Consumption: 2 W
- Dimensions: 450(W) × 353.5(D) × 142.7(H) mm
- Weight: 8 kg

Incl.: Platter, counterweight, slip mat, slip sheet, power cable, RCA cable and instruction manual, *(headshell and cartridge sold separately)*