

## MARTIN AUDIO ACS-55TS-W

Šifra: 20973

Kategorija proizvoda: Plafonski Zvučnici

Proizvođač: Martin Audio



**Cena: 21.480,00 rsd**

### Features

- Compact two-way ceiling speaker, shallow backcan
- 5.25" (135mm) LF driver and 0.75" (19mm) HF dome tweeter
- Wide 150° conical coverage pattern reduces speaker count required for even coverage
- 70V/100V multi-tap line transformer or 16-ohm low-impedance operation
- Low and high-frequency overload protection
- UL94V-0 rated baffle with zinc-plated steel backcan
- Quick release, bezel-less grille
- Tile rails and C-ring included
- 5-year warranty
- UL 1480A and UL 2043 compliant

### Applications

- Retail outlets
- Cafes, bars and restaurants
- Museums and Houses of Worship
- Hotels, casinos and concourses
- Transportation facilities
- Boardrooms and reception areas

**TYPE:** Compact, passive two-way ceiling speaker, ported bass reflex

**FREQUENCY RESPONSE:** 117Hz-20kHz  $\pm$  3dB -10dB @ 79Hz

### DRIVERS:

- LF: 5.25" /1" high-temp voice coil, coated paper cone, rubber surround, ferrite motor, pressed steel chassis
- HF: 0.75" silk dome, neodymium motor

**RATED POWER:** 50W AES, 200W peak

**RECOMMENDED AMPLIFIER:** VIA2004 (for low-impedance operation)

**SENSITIVITY:** 90dB / 1W(4V) / 1m

**MAXIMUM SPL:** 113dB peak

**NOMINAL IMPEDANCE:** 16 $\Omega$

**DISPERSION (-6dB):** 150° conical up to 7kHz

**CROSSOVER:** 3kHz passive (LF and HF auto-resetting fuses)

### TRANSFORMER TAPS:

- 70V: 30w / 15w / 7.5w / 3.75w
- 100V: 30w / 15w / 7.5w

**RECOMMENDED HIGH-PASS FILTER:** 65Hz 24dB/oct

**ENCLOSURE:** UL 94V-0 rated ABS baffle with steel backcan

**FINISH:** Baffle and grille: RAL9016 white Backcan: zinc plated

**GRILLE:** Perforated steel, powder-coated, bayonet fitting

**CONNECTORS:** Ceramic connector (in and link) located behind fire-retardant steel cover

**ACCESSORIES (included):**

- 2 tile rails
- C-ring backing plate
- Cut-out template

**DIMENSIONS:**

- (OD) 245mm x (D) Back Can 100mm, (D) Inc. Grille 118mm
- (OD) 9.7in x (D) Back Can 3.95in, (D) Inc. Grille 4.65in

**HOLE CUT-OUT DIMENSION:** 222mm (8.74") diameter

**WEIGHT:** 2.8kg (6.2lbs)

**CEILING SAFETY STANDARDS:** Certified compliant: UL 1480A, UL 2043