

Biamp AMP-D225H

Šifra: 21131

Kategorija proizvoda: Pa Rack Ostalo

Proizvođač: Biamp



Cena: 66.000,00 rsd

GENERAL

Height: 1.5 inches (37 mm)

Width: 8.6 inches (218 mm)

Depth: 2.8 inches (70 mm)

Weight: 1.1 lbs (0.5 kg)

ENVIRONMENTAL

Ambient Operating Temperature Range: 32 - 86° F (0 - 30° C)

Humidity: 10-90% relative humidity (non-condensing)

Altitude: 0-6,600 ft (0-2000m) MSL

POWER

Power: 24V DC 50W

Cooling: Convection

NETWORK

Network Connection(s): RJ-45 with Ethernet (CAT5e or better)

CONTROLS & INDICATORS

RS-232:

- Number of Ports: 2 (bidirectional)
- Connector: 3-pin, 0.3-inch Euroblock
- Baud Rate: 1200 - 115200 bit/sec
- Data Bits: 7, 8
- Parity: Even, Odd, None
- Stop Bits: 1, 2
- IR Frequency Range: 400 Hz to 500 kHz

Connectivity:

INPUTS

- Number of Inputs: 4 (stereo)
- Connector: RCA
- Input Impedance: < 100kΩ
- Max Input Level: 2 Vrms
- Input Gain (adjustable): ± 12 dB
- Wake on Signal: Adjustable level

OUTPUTS

- Number of Channels: 2
- Maximum Rated Output:
- Single Channel, 4Ω: 35W

- Single Channel, 8 Ω : 25W
- Bridged, 4 Ω : 55W
- Bridged, 8 Ω : 35W
- Minimum Operational Load: 2 Ω
- THD+N (20 Hz - 20 kHz, @ 1W): < 0.1 %
- Connector: 4-pin, 0.3-inch Euroblock

USB

- Connector: USB 2.0 Type-B
- Bit Depth: 16-bit
- Sample Rate: 48kHz

GPIO

- Number of Ports: 4
- Connector: 5-pin, 0.3-inch Euroblock
- Type: Open drain
- Input Trigger Low: < 1V DC
- Input Trigger High: > 4V DC
- Isolated Output: No
- Max Voltage: 24V DC
- Max Current: 0.5

AMPLIFIER

Channels: 2 Channels

COMPLIANCE

Environmental Ratings:

- FCC Part 15B (USA)
- UL listed (USA and Canada)
- CE Marked (Europe)
- RoHS Directive (Europe)