

## Biamp AMP-D225H

Šifra: 21131  
Kategorija proizvoda: Pa Rack Ostalo  
Proizvođač: Biamp

**Cena: 66.000,00 rsd**

**Humidity:** 10-90% relative humidity (non-condensing)  
**Altitude:** 0-6,600 ft (0-2000m) MSL

### POWER

**Power:** 24V DC 50W  
**Cooling:** Convection

### NETWORK

**Network Connection(s):** RJ-45 with Ethernet (CAT5e or better)

### CONTROLS & INDICATORS

#### RS-232:

- Number of Ports: 2 (bidirectional)
- Connector: 3-pin, 0.3-inch Euroblock
- Baud Rate: 1200 - 115200 bit/sec
- Data Bits: 7, 8
- Parity: Even, Odd, None
- Stop Bits: 1, 2
- IR Frequency Range: 400 Hz to 500 kHz

#### Connectivity:

#### INPUTS

- Number of Inputs: 4 (stereo)
- Connector: RCA
- Input Impedance: < 100kΩ
- Max Input Level: 2 Vrms
- Input Gain (adjustable): ± 12 dB
- Wake on Signal: Adjustable level

#### OUTPUTS

- Number of Channels: 2
- Maximum Rated Output:
- Single Channel, 4Ω: 35W
- Single Channel, 8Ω: 25W
- Bridged, 4Ω: 55W
- Bridged, 8Ω: 35W
- Minimum Operational Load: 2Ω
- THD+N (20 Hz - 20 kHz, @ 1W): < 0.1 %
- Connector: 4-pin, 0.3-inch Euroblock

#### USB

- Connector: USB 2.0 Type-B
- Bit Depth: 16-bit
- Sample Rate: 48kHz

#### GPIO

Biamp AMP-D225H unknown

### GENERAL

**Height:** 1.5 inches (37 mm)  
**Width:** 8.6 inches (218 mm)  
**Depth:** 2.8 inches (70 mm)  
**Weight:** 1.1 lbs (0.5 kg)

### ENVIRONMENTAL

**Ambient Operating Temperature Range:** 32 - 86° F (0 - 30° C)

- Number of Ports: 4
- Connector: 5-pin, 0.3-inch Euroblock
- Type: Open drain
- Input Trigger Low: < 1V DC
- Input Trigger High: > 4V DC
- Isolated Output: No
- Max Voltage: 24V DC
- Max Current: 0.5

## **AMPLIFIER**

**Channels:** 2 Channels

## **COMPLIANCE**

### **Environmental Ratings:**

- FCC Part 15B (USA)
- UL listed (USA and Canada)
- CE Marked (Europe)
- RoHS Directive (Europe)