

ONKYO A-50 Black

Šifra: 21490

Kategorija proizvoda: Integrisana Pojačala

Proizvođač: Onkyo



Cena: 155.880,00 rsd

Inverted Darlington Amplifier

A three-stage Inverted Darlington Amplifier drives high current signals with minimal distortion, so your content is just as clear and strong as the artists intended.

Dynamic Intermodulation Distortion Reduction Circuitry (DIDRC)

Thanks to patented DIDRC circuitry (Dynamic Intermodulation Distortion Reduction Circuitry), the Onkyo A-50 Integrated Amplifier delivers a vivid yet smooth and comfortable sound from any musical source. DIDRC is a discrete signal control circuit designed to embody Onkyo's sound philosophy, used in the analog filter of the DAC. DIDRC's high slew-rate design reduces noise generated in very high frequency bands of digital sources, resulting in cleaner, clearer audio.

Aluminum front panel

A 5mm-thick extruded aluminum front panel is used to increase rigidity and suppress vibration.

An oval chassis

The "oval chassis" with oval press lines strengthens the bottom surface and disperses vibration.

Fan-less design

Combined with a fan-less design that eliminates noise, a premium stereo DAC (32bit / 768kHz) that reduces distortion, and an extrusion aluminum heat sink for vibration suppression, this amplifier provides an exquisite and powerful sound.

High quality capacitors

High-quality 10000uF capacitors custom-made exclusively for Onkyo, a copper bus bar, and rigid front panels further reduce vibration and signal degradation.

OUTPUT POWER:

- 110w (8ohm, 20-20kHz, THD 0.07%, 2ch driven)
- 180w (4ohm, 1kHz, THD 0.7%, 2ch driven)

AMPLIFIER CHANNEL: 2 Ch

PRE AMPLIFIER CHANNEL: 2 Ch

AMPLIFIER TYPE: Class AB

FREQUENCY RESPONSE: 5Hz~100kHz (+1/-3dB)

TONE CONTROL (BASS / TREBLE): 100Hz \pm 10dB / 10kHz \pm 10dB

SPEAKER IMPEDANCE: 4-16 Ω

ANALOG AUDIO INPUT: RCA (Unbalanced) x 3 Pair

DIGITAL AUDIO INPUT: HDMI ARC, COAX, Optical x 2 , USB-A (Storage playback)

PHONO INPUT: 1 Pair (MM/MC)

AUDIO PRE OUTPUT: RCA(Unbalanced) x 1 Pair

HEADPHONE OUTPUT: 1/4" (6.3mm) Jack

SETUP MIC INPUT: 1/8" (3.5mm) Jack

NETWORK CONNECTIVITY: Wi-Fi, LAN

BLUETOOTH: SBC, aptX, aptX HD

ROOM CALIBRATION: Dirac Live® Room Correction (Full version is option)

PRODUCT DIMENSIONS (W X H X D): 17.1" (435mm) x 5.3" (135mm) x 14.0" (355mm)

PRODUCT WEIGHT: 13.0 kg

PACKAGE DIMENSIONS (W X H X D): 21.3" (542mm) x 9.3" (236mm) x 17.4" (441mm)

POWER CONSUMPTION: 350w, 47w (idle), Less than 0.3w (Standby)