

PSI Audio A25-Ms Red

Šifra: 22017
Kategorija proizvoda:
Proizvođač: PSI Audio

Cena: 898.800,00 rsd



A25-M - REFERENCE-GRANDE PRECISION AND NATURAL SOUND

The A25-M is PSI Audio's flagship three-way active studio monitor, designed for professionals and serious enthusiasts who demand the highest level of accuracy, imaging, and neutrality in their listening environment. With breakthrough driver technology and a fully analog signal path, the A25-M delivers sound so true to the source that the speakers seem to disappear - letting you focus on what matters most: your mix.

At the heart of the A25-M is an innovative Extended Dome Driver (EXD)-based midrange developed entirely in-house, combining the strengths of dome and cone designs to achieve higher SPL with lower distortion and exceptional coherence across the mid frequencies. This advanced three-way architecture provides a flat frequency response from 28 Hz to 23 kHz and a remarkably stable and lifelike stereo image - ideal for critical listening, mastering, and immersive audio work.

A25-M TECHNICAL DATA

Data	A25-M	[Unit]
Potential peak power	330 + 130 + 55	W
Continuous max SPL@1 m	111	dB

Data	A25-M	[Unit]
Short term max. SPL@1m	114	dB
Peak max. SPL@1m	124	dB
Signal to noise ratio (S/N)	102	dB
Bandwidth at -6dB	28-23'000	Hz
SPL tolerances	±1.2	dB
Phase tolerances	± 45 (180 Hz - 20 kHz)	deg
Dispersion (H x V)	80 x 40	deg
System	3	ways
Crossover frequency	400, 3'300	Hz
Woofers ext. diam.	290	mm
Woofers ext. diam.	11.4	in
W. diaphragm diam.	210	mm
W. diaphragm diam.	8.3	in
Tweeter ext. dim.	100	mm
Tweeter ext. dim.	3.9	in
T. diaphragm diam.	27	mm
T. diaphragm diam.	1.06	in
Dimensions W x H x D	320 x 590 x 380	mm
Dimensions W x H x D	12.6 x 23.3 x 15.0	in
Net Weight	27.2	Kg
Net Weight	59.9	lbs
Input connector	1 x XLR F / 3P	