Firma: Player Plus doo
Adresa: Svetogorska 9
Telefon: +381 11 3347 442
Fax: +381 11 3347 615
PIB: 106966344
E-mail: porudzbine@player.rs

Focusrite ISA C8X USB Zvučna Kartica



Šifra: 22033
Kategorija prozivoda: USB Zvučne kartice
Proizvođač: Focusrite

Cena: 239.880,00 rsd

Key features
• 2U rack-mounted, 26-in/28-out USB-C audio interface
• Eight remote-controlled preamps with up to 79dB of gain, two of which are ISA preamps with Lundahl LL1538 transformers
• All-analogue Console and 430 Air modes for tonal shaping
• 24-bit/192kHz AD/DA conversion with up to 125dB of dynamic range
• Additional Sonnox bundles available

Hardware Overview
Microphone Preamps: 8
Phantom Power: Yes (Independent per-channel)
Line Inputs: 8
Instrument Inputs: 2
Insert Sends: 2
Insert Returns: 2
Line Outputs: 12
Headphone Outputs: 2
Line Outputs: 10
Headphone Outputs: 2
ADAT Inputs: 2 (16 channels at 44.1/48kHz and up to 8 channels at 96kHz)
ADAT Outputs: 2 (16 channels at 44.1/48kHz and up to 8 channels at 96kHz)
SPDIF Input: 1 (2 channels at 96kHz)
SPDIF Output: 1 (2 channels at 96kHz)
MIDI Input: 1
MIDI Output: 1
Word Clock Input: 1
Word Clock Output: 1
Talkback: Yes
Loopback: Yes
Connectivity: USB Type-C
Protocol: USB 2.0
Form Factor: Rack Mountable (2U)
Simultaneous I/O: 26x28 (including Loopback)
A/D Resolution: 24-bit/192 kHz
Maximum Power Draw: 40W
Bus Powered: N

ISA Microphone Inputs (Channels 1-2)
Frequency Response: 20Hz-20kHz (±0.4dB)
Dynamic Range (A-weighted): 117dB
THD+N (minimum at minimum gain): -93dB (0.00023%)
Noise EIN (A-Weighted): -128dB
Maximum Input Level (minimum gain, Low impedance): +16dBu
Gain Range: 79dB
Input Impedance (switchable): 800Ω (Low), 1400Ω (ISA 110), 2400Ω (Med), 7000Ω (High)
High Pass Filter (HPF): 75Hz cut-off frequency, 18dB/Octave

Microphone Inputs (Channels 3-8)
Frequency Response: 20Hz-20kHz (±0.1dB)
Dynamic Range (A-weighted): 116dB
THD+N (minimum at 8dB Gain): -100dB (0.001%)
Noise EIN (A-Weighted): -127dB
Maximum Input Level (minimum gain): +16dBu
Gain Range: 69dB
Input Impedance: 3200Ω

Fixed-level Line Inputs (Channels 1-8)
Frequency Response: 20Hz-20kHz (±0.05dB)
Dynamic Range (A-weighted): 120dB
THD+N (minimum): < -105dB (0.00056%)
Maximum Input Level: +24dBu

Instrument Inputs (Channels 1-2)
Frequency Response: 20Hz-20kHz (±0.5dB)
Dynamic Range (A-weighted): 117dB
THD+N (minimum): -89dB (0.0036%)
Maximum Input Level (at minimum gain): +15dBu
Gain Range: 79dB
Input Impedance (switchable): 400kΩ (Low), 1.2MΩ (High)

Inserts (Channels 1-2)
Connection: Balanced
Maximum Output Level (send): +16dBu
Maximum Input Level (return): +16dBu

Line Outputs
Frequency Response: 20Hz-20kHz (±0.02dB)
Dynamic Range (A-weighted): 125dB
THD+N (minimum): -113dB (0.00023%)
Maximum Output Level: +24dBu

Headphone Outputs
Frequency Response: 20Hz-20kHz (±0.1dB)
Dynamic Range: 114dB @ 33Ω, 116dB @ 300Ω, 116dB @ 600Ω
THD+N: -102dB @ 33Ω, -110dB @ 300Ω, -110dB @ 600Ω
Max Output Level: +8dBu @ 33Ω, +11dBu @ 300Ω, +11dBu @ 600Ω
Max Output Power: 130mW @ 33Ω, 28mW @ 300Ω, 14mW @ 600Ω
Output Impedance: 3Ω

Compatibility
Windows: Intel, AMD, and Arm64 processors supported
MacOS: Apple Silicon and Intel processors supported

Dimensions
Width: 482.6 mm (19.00 in)
Depth: 292.8 mm (11.53 in)
Height: 89 mm (3.50 in)
Weight: 5.558 kg (12.26 lbs)

Power Requirements
External: 40W

What's in the Box?
• ISA C8X audio interface
• 1.5mm USB type C-to-C cable
• Region-specific IEC cable
• Rubber feet (x4)

Cene su informativnog karaktera. Prodavac ne odgovara za tačnost cena iskazanih na sajtu, zadržava pravo izmena cena. Ponudu za ostale artikle, informacije o stanju lagera i aktuelnim cenama možete dobiti na upit. Plaćanje se isključivo vrši virmanski - bezgotovinski.